

Idaho Transportation Department

Monthly WIM Distribution for Sep-2023

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	27	3,070	1,706	22	100	198	16	71	103	46	1	2	17	0
	Flex	.03	.00	.00	.36	.36	.63	.20	.27	1.43	.66	.11	1.03	1.13	0.00
	Rigid	.07	.00	.00	.43	.38	1.22	.55	.35	2.74	1.67	.17	2.16	2.07	0.00
	GVW	7.9	3.2	4.9	17.8	16.5	33.1	38.2	22.6	58.6	78.3	32.1	62.1	79.4	0.0
N	Num	4	1,793	1,050	7	53	131	9	40	57	14	1	1	7	0
	Flex	.11	.00	.00	.79	.26	.62	.30	.16	1.23	.87	.05	1.76	1.60	0.00
	Rigid	.24	.00	.00	.94	.28	1.16	.89	.21	2.25	2.08	.05	3.93	2.77	0.00
	GVW	11.1	3.1	4.8	29.5	16.8	34.4	44.7	22.5	59.2	76.4	24.2	87.2	82.6	0.0
S	Num	23	1,277	656	15	47	67	8	31	46	32	1	2	9	0
	Flex	.02	.00	.00	.17	.45	.66	.10	.38	1.66	.58	.11	.51	.75	0.00
	Rigid	.03	.00	.00	.20	.48	1.33	.25	.52	3.31	1.52	.17	.94	1.53	0.00
	GVW	7.1	3.4	4.9	13.5	16.1	30.6	32.9	21.8	57.4	79.5	32.9	49.2	76.3	0.0
N Lane1	Num	4	1,793	1,050	7	53	131	9	40	57	14	1	1	7	0
	Flex	.11	.00	.00	.79	.26	.62	.30	.16	1.23	.87	.05	1.76	1.60	0.00
	Rigid	.24	.00	.00	.94	.28	1.16	.89	.21	2.25	2.08	.05	3.93	2.77	0.00
	GVW	11.1	3.1	4.8	29.5	16.8	34.4	44.7	22.5	59.2	76.4	24.2	87.2	82.6	0.0
S Lane1	Num	23	1,277	656	15	47	67	8	31	46	32	1	2	9	0
	Flex	.02	.00	.00	.17	.45	.66	.10	.38	1.66	.58	.11	.51	.75	0.00
	Rigid	.03	.00	.00	.20	.48	1.33	.25	.52	3.31	1.52	.17	.94	1.53	0.00
	GVW	7.1	3.4	4.9	13.5	16.1	30.6	32.9	21.8	57.4	79.5	32.9	49.2	76.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2023

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9