Idaho Transportation Department

Monthly WIM Distribution for Mar-2019

Site names: 00138
County: Owyhee
Funct Class: R Principal Arterial - Other
Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
Daily Factor Grp: 4
Axle Factor Grp: 2
Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	3	659	599	14	71	9	1	9	397	11	10	6	21	0
	Flex	.00	.00	.00	.28	.10	.26	.44	.18	.65	.32	.67	.49	.63	0.00
	Rigid	.00	.00	.00	.32	.10	.32	.77	.18	1.10	.58	.64	.50	.84	0.00
	GVW	3.7	3.4	6.4	21.8	17.1	22.7	41.3	26.3	55.0	53.1	46.4	50.3	64.1	0.0
E	Num	3	335	311	7	32	5	1	5	196	7	6	3	11	0
	Flex	.00	.00	.00	.27	.08	.17	.33	.19	.45	.25	.90	.48	.63	0.00
	Rigid	.00	.00	.00	.28	.08	.20	.39	.19	.71	.43	.86	.48	.78	0.00
	GVW	3.4	3.3	6.3	21.1	17.2	20.9	35.4	26.4	49.8	49.3	54.1	55.3	61.4	0.0
W	Num	2	325	288	7	39	4	1	4	201	5	5	3	10	0
	Flex	.00	.00	.00	.30	.11	.42	.41	.15	.85	.47	.47	.50	.59	0.00
	Rigid	.00	.00	.00	.36	.11	.53	.78	.15	1.50	.87	.45	.51	.90	0.00
	GVW	4.0	3.5	6.6	22.2	17.0	26.2	42.7	25.1	60.0	58.8	40.4	46.3	66.1	0.0
E Lane1	Num	3	335	311	7	32	5	1	5	196	7	6	3	11	0
	Flex	.00	.00	.00	.27	.08	.17	.33	.19	.45	.25	.90	.48	.63	0.00
	Rigid	.00	.00	.00	.28	.08	.20	.39	.19	.71	.43	.86	.48	.78	0.00
	GVW	3.4	3.3	6.3	21.1	17.2	20.9	35.4	26.4	49.8	49.3	54.1	55.3	61.4	0.0
W Lane1	Num	2	325	288	7	39	4	1	4	201	5	5	3	10	0
	Flex	.00	.00	.00	.30	.11	.42	.41	.15	.85	.47	.47	.50	.59	0.00
	Rigid	.00	.00	.00	.36	.11	.53	.78	.15	1.50	.87	.45	.51	.90	0.00
	GVW	4.0	3.5	6.6	22.2	17.0	26.2	42.7	25.1	60.0	58.8	40.4	46.3	66.1	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 04/03/2019 1:14 PM

Idaho Transportation Department

Monthly WIM Distribution for Mar-2019

Site names:	00138	Seasonal Factor Grp:	4
County:	Owyhee	Daily Factor Grp:	4
Funct Class:	R Principal Arterial - Other	Axle Factor Grp:	2
Location:	US-95 3.6 Mi. S of Jct SH-55	Growth Factor Grp:	

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 04/03/2019 1:14 PM