

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	502	443	11	100	8	1	11	372	8	9	6	18	0
	Flex	.00	.00	.00	.65	.10	.65	.30	.53	1.71	.96	2.13	1.33	1.47	0.00
	Rigid	.00	.00	.00	.76	.10	.92	.74	.62	3.20	2.02	2.27	1.48	2.06	0.00
	GVW	1.5	3.8	6.5	24.5	16.1	29.6	51.9	31.5	62.6	66.0	57.8	59.5	72.0	0.0
E	Num	1	253	261	6	16	4	0	5	190	4	4	3	9	0
	Flex	.00	.00	.00	.17	.04	.20	0.00	.16	.29	.17	.67	.32	.45	0.00
	Rigid	.00	.00	.00	.17	.04	.25	0.00	.16	.46	.29	.63	.33	.52	0.00
	GVW	1.7	3.3	6.0	19.5	16.0	24.7	0.0	26.9	45.1	47.6	50.2	50.3	59.3	0.0
W	Num	1	249	182	5	83	3	1	6	182	4	5	3	9	0
	Flex	.00	.00	.00	1.13	.11	1.13	.30	.87	3.10	1.81	3.29	1.97	2.79	0.00
	Rigid	.00	.00	.00	1.36	.11	1.61	.74	1.04	5.90	3.79	3.56	2.22	3.99	0.00
	GVW	1.3	4.4	7.3	29.6	16.1	36.1	51.9	36.4	80.2	82.6	63.2	65.6	85.4	0.0
E Lane1	Num	1	253	261	6	16	4	0	5	190	4	4	3	9	0
	Flex	.00	.00	.00	.17	.04	.20	0.00	.16	.29	.17	.67	.32	.45	0.00
	Rigid	.00	.00	.00	.17	.04	.25	0.00	.16	.46	.29	.63	.33	.52	0.00
	GVW	1.7	3.3	6.0	19.5	16.0	24.7	0.0	26.9	45.1	47.6	50.2	50.3	59.3	0.0
W Lane1	Num	1	249	182	5	83	3	1	6	182	4	5	3	9	0
	Flex	.00	.00	.00	1.13	.11	1.13	.30	.87	3.10	1.81	3.29	1.97	2.79	0.00
	Rigid	.00	.00	.00	1.36	.11	1.61	.74	1.04	5.90	3.79	3.56	2.22	3.99	0.00
	GVW	1.3	4.4	7.3	29.6	16.1	36.1	51.9	36.4	80.2	82.6	63.2	65.6	85.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9