

Idaho Transportation Department

Monthly WIM Distribution for Jun-2022

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	51	1,249	780	7	67	75	8	60	419	33	18	10	6	0
	Flex	.01	.00	.00	.54	.31	.31	.24	.15	.85	.64	.98	.71	1.54	0.00
	Rigid	.03	.00	.00	.74	.30	.55	.68	.18	1.56	1.55	.94	.94	2.44	0.00
	GVW	10.7	2.7	5.1	34.1	18.6	30.2	42.8	23.1	61.0	76.3	53.9	62.7	81.5	0.0
E	Num	11	655	408	3	34	19	8	31	219	18	10	4	3	0
	Flex	.02	.00	.00	.53	.37	.35	.32	.16	.88	.98	1.38	.56	1.75	0.00
	Rigid	.03	.00	.00	.71	.37	.60	.96	.20	1.61	2.45	1.33	.60	2.47	0.00
	GVW	11.8	2.8	5.3	38.4	20.3	32.1	51.0	24.5	62.4	86.6	60.1	57.9	84.9	0.0
W	Num	40	595	373	5	33	56	3	29	200	15	8	6	4	0
	Flex	.01	.00	.00	.53	.24	.30	.22	.13	.82	.50	.57	.83	1.21	0.00
	Rigid	.03	.00	.00	.71	.24	.54	.58	.15	1.53	1.15	.54	1.17	2.22	0.00
	GVW	10.4	2.5	4.7	32.2	16.9	29.5	37.6	21.4	59.6	67.0	47.4	66.1	75.9	0.0
E Lane1	Num	11	655	408	3	34	19	8	31	219	18	10	4	3	0
	Flex	.02	.00	.00	.53	.37	.35	.32	.16	.88	.98	1.38	.56	1.75	0.00
	Rigid	.03	.00	.00	.71	.37	.60	.96	.20	1.61	2.45	1.33	.60	2.47	0.00
	GVW	11.8	2.8	5.3	38.4	20.3	32.1	51.0	24.5	62.4	86.6	60.1	57.9	84.9	0.0
W Lane1	Num	40	595	373	5	33	56	3	29	200	15	8	6	4	0
	Flex	.01	.00	.00	.53	.24	.30	.22	.13	.82	.50	.57	.83	1.21	0.00
	Rigid	.03	.00	.00	.71	.24	.54	.58	.15	1.53	1.15	.54	1.17	2.22	0.00
	GVW	10.4	2.5	4.7	32.2	16.9	29.5	37.6	21.4	59.6	67.0	47.4	66.1	75.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2022

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9