

Idaho Transportation Department

Monthly WIM Distribution for Jul-2022

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	15	1,199	742	6	67	32	2	50	450	20	19	10	9	0
	Flex	.01	.00	.00	.58	.24	.26	.27	.13	.70	.49	1.64	.64	1.19	0.00
	Rigid	.03	.00	.00	.82	.23	.44	.61	.15	1.26	1.18	1.67	.82	1.92	0.00
	GVW	10.5	2.8	5.1	40.0	18.2	28.7	48.6	23.4	59.6	73.7	58.9	63.8	79.9	0.0
E	Num	2	606	372	3	33	9	2	25	230	12	10	5	6	0
	Flex	.01	.00	.00	.61	.29	.28	.34	.15	.76	.53	2.66	.58	1.59	0.00
	Rigid	.03	.00	.00	.82	.28	.44	.84	.18	1.38	1.34	2.77	.66	2.51	0.00
	GVW	10.9	3.0	5.6	41.0	19.4	30.1	53.2	24.9	61.5	80.1	66.5	60.3	92.3	0.0
W	Num	13	593	370	4	34	24	1	25	219	9	10	6	4	0
	Flex	.01	.00	.00	.48	.20	.24	.23	.10	.64	.42	.73	.66	.60	0.00
	Rigid	.03	.00	.00	.68	.19	.43	.50	.12	1.17	.96	.70	.93	1.08	0.00
	GVW	10.3	2.5	4.7	36.6	17.2	27.9	44.1	21.9	57.8	66.8	51.2	65.8	60.2	0.0
E Lane1	Num	2	606	372	3	33	9	2	25	230	12	10	5	6	0
	Flex	.01	.00	.00	.61	.29	.28	.34	.15	.76	.53	2.66	.58	1.59	0.00
	Rigid	.03	.00	.00	.82	.28	.44	.84	.18	1.38	1.34	2.77	.66	2.51	0.00
	GVW	10.9	3.0	5.6	41.0	19.4	30.1	53.2	24.9	61.5	80.1	66.5	60.3	92.3	0.0
W Lane1	Num	13	593	370	4	34	24	1	25	219	9	10	6	4	0
	Flex	.01	.00	.00	.48	.20	.24	.23	.10	.64	.42	.73	.66	.60	0.00
	Rigid	.03	.00	.00	.68	.19	.43	.50	.12	1.17	.96	.70	.93	1.08	0.00
	GVW	10.3	2.5	4.7	36.6	17.2	27.9	44.1	21.9	57.8	66.8	51.2	65.8	60.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2022

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9