

Idaho Transportation Department

Monthly WIM Distribution for Oct-2022

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	15	904	812	7	61	33	3	50	464	33	19	10	14	0
	Flex	.04	.00	.00	.96	.33	.41	.54	.15	1.22	.61	1.54	1.08	1.53	0.00
	Rigid	.09	.00	.00	1.40	.33	.75	1.38	.17	2.32	1.45	1.50	1.68	2.51	0.00
	GVW	13.4	2.8	5.1	43.6	18.8	32.2	58.1	23.7	67.5	74.6	61.1	71.6	87.3	0.0
E	Num	2	456	412	3	30	9	3	26	240	16	10	4	9	0
	Flex	.02	.00	.00	1.02	.32	.29	.65	.17	1.07	.65	2.11	.92	1.84	0.00
	Rigid	.04	.00	.00	1.47	.32	.48	1.60	.19	2.00	1.64	2.07	1.18	2.91	0.00
	GVW	11.9	2.8	5.3	43.8	19.1	30.0	63.0	24.7	65.6	81.3	67.8	69.1	92.9	0.0
W	Num	13	448	400	4	31	24	2	24	225	17	9	6	5	0
	Flex	.05	.00	.00	.91	.34	.45	.51	.12	1.39	.58	1.02	1.20	1.09	0.00
	Rigid	.10	.01	.00	1.36	.34	.85	1.24	.15	2.70	1.29	.98	2.02	1.97	0.00
	GVW	13.5	2.7	4.9	42.6	18.5	33.1	53.5	22.6	69.5	68.8	54.4	73.9	76.9	0.0
E Lane1	Num	2	456	412	3	30	9	3	26	240	16	10	4	9	0
	Flex	.02	.00	.00	1.02	.32	.29	.65	.17	1.07	.65	2.11	.92	1.84	0.00
	Rigid	.04	.00	.00	1.47	.32	.48	1.60	.19	2.00	1.64	2.07	1.18	2.91	0.00
	GVW	11.9	2.8	5.3	43.8	19.1	30.0	63.0	24.7	65.6	81.3	67.8	69.1	92.9	0.0
W Lane1	Num	13	448	400	4	31	24	2	24	225	17	9	6	5	0
	Flex	.05	.00	.00	.91	.34	.45	.51	.12	1.39	.58	1.02	1.20	1.09	0.00
	Rigid	.10	.01	.00	1.36	.34	.85	1.24	.15	2.70	1.29	.98	2.02	1.97	0.00
	GVW	13.5	2.7	4.9	42.6	18.5	33.1	53.5	22.6	69.5	68.8	54.4	73.9	76.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2022

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9