

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2022

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	14	754	362	5	30	34	2	21	341	11	17	7	8	0
	Flex	.03	.01	.01	.75	.32	.47	.30	.33	1.44	1.02	3.10	2.15	2.10	0.00
	Rigid	.08	.01	.01	1.16	.32	.89	.72	.42	2.82	2.63	3.23	2.92	3.76	0.00
	GVW	13.9	4.7	5.1	42.9	18.2	34.6	44.8	29.4	71.2	90.4	69.7	82.2	96.4	0.0
E	Num	2	454	122	2	12	9	2	9	158	6	8	3	5	0
	Flex	.04	.01	.02	.81	.48	.46	.29	.54	1.42	1.04	5.56	3.40	2.03	0.00
	Rigid	.11	.01	.02	1.24	.49	.88	.78	.70	2.79	2.69	5.99	4.33	3.52	0.00
	GVW	15.4	5.8	6.8	44.3	20.2	37.1	47.4	34.5	69.2	89.7	81.9	88.4	96.2	0.0
W	Num	12	299	240	4	18	25	1	13	183	5	10	4	4	0
	Flex	.04	.01	.00	.66	.24	.47	.69	.20	1.40	.89	1.49	1.56	1.91	0.00
	Rigid	.08	.01	.00	.97	.23	.87	1.34	.25	2.74	2.34	1.45	2.28	3.63	0.00
	GVW	13.8	2.9	4.5	39.8	17.0	33.4	50.2	26.4	71.1	89.1	61.3	79.8	94.5	0.0
E Lane1	Num	2	454	122	2	12	9	2	9	158	6	8	3	5	0
	Flex	.04	.01	.02	.81	.48	.46	.29	.54	1.42	1.04	5.56	3.40	2.03	0.00
	Rigid	.11	.01	.02	1.24	.49	.88	.78	.70	2.79	2.69	5.99	4.33	3.52	0.00
	GVW	15.4	5.8	6.8	44.3	20.2	37.1	47.4	34.5	69.2	89.7	81.9	88.4	96.2	0.0
W Lane1	Num	12	299	240	4	18	25	1	13	183	5	10	4	4	0
	Flex	.04	.01	.00	.66	.24	.47	.69	.20	1.40	.89	1.49	1.56	1.91	0.00
	Rigid	.08	.01	.00	.97	.23	.87	1.34	.25	2.74	2.34	1.45	2.28	3.63	0.00
	GVW	13.8	2.9	4.5	39.8	17.0	33.4	50.2	26.4	71.1	89.1	61.3	79.8	94.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2022

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9