

Idaho Transportation Department

Monthly WIM Distribution for Jan-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	12	569	395	3	33	30	3	26	369	13	17	9	6	0
	Flex	.03	.01	.00	.94	.31	.43	1.38	.32	1.33	.77	2.95	1.71	1.38	0.00
	Rigid	.05	.01	.00	1.34	.30	.82	3.77	.40	2.55	2.00	3.09	2.38	2.55	0.00
	GVW	13.2	4.3	5.1	45.2	18.3	34.2	73.2	30.4	69.8	85.2	67.5	79.4	90.6	0.0
E	Num	2	328	159	2	13	8	1	11	176	6	8	4	4	0
	Flex	.01	.02	.01	.82	.43	.34	2.48	.49	1.29	.81	4.67	1.86	1.26	0.00
	Rigid	.03	.02	.01	1.14	.42	.65	6.61	.62	2.48	2.16	5.00	2.25	2.35	0.00
	GVW	11.7	5.1	6.2	43.1	20.4	34.4	84.7	35.5	68.9	86.0	76.8	78.2	86.2	0.0
W	Num	10	240	235	3	20	21	2	14	194	7	9	5	3	0
	Flex	.03	.01	.00	.99	.24	.46	.69	.20	1.37	.73	1.28	1.47	1.52	0.00
	Rigid	.06	.01	.00	1.44	.24	.87	1.80	.24	2.62	1.88	1.24	2.32	2.70	0.00
	GVW	13.4	3.0	4.7	47.7	17.3	33.8	64.6	26.7	70.6	82.5	58.0	78.5	92.8	0.0
E Lane1	Num	2	328	159	2	13	8	1	11	176	6	8	4	4	0
	Flex	.01	.02	.01	.82	.43	.34	2.48	.49	1.29	.81	4.67	1.86	1.26	0.00
	Rigid	.03	.02	.01	1.14	.42	.65	6.61	.62	2.48	2.16	5.00	2.25	2.35	0.00
	GVW	11.7	5.1	6.2	43.1	20.4	34.4	84.7	35.5	68.9	86.0	76.8	78.2	86.2	0.0
W Lane1	Num	10	240	235	3	20	21	2	14	194	7	9	5	3	0
	Flex	.03	.01	.00	.99	.24	.46	.69	.20	1.37	.73	1.28	1.47	1.52	0.00
	Rigid	.06	.01	.00	1.44	.24	.87	1.80	.24	2.62	1.88	1.24	2.32	2.70	0.00
	GVW	13.4	3.0	4.7	47.7	17.3	33.8	64.6	26.7	70.6	82.5	58.0	78.5	92.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9