

Idaho Transportation Department

Monthly WIM Distribution for Mar-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	12	800	452	6	41	30	2	34	390	13	16	9	10	0
	Flex	.02	.00	.00	.73	.36	.41	.49	.30	1.36	.89	1.94	1.69	1.49	0.00
	Rigid	.05	.00	.00	1.13	.35	.75	1.31	.36	2.60	2.22	1.94	2.34	2.75	0.00
	GVW	12.9	4.8	5.6	40.1	19.4	33.0	57.7	28.9	70.3	85.1	62.4	77.8	91.6	0.0
E	Num	2	466	180	3	20	8	1	18	197	6	7	4	5	0
	Flex	.01	.00	.01	1.03	.49	.40	.22	.46	1.48	.88	3.02	2.28	1.80	0.00
	Rigid	.03	.00	.01	1.63	.49	.74	.62	.54	2.84	2.24	3.08	2.72	3.12	0.00
	GVW	10.7	6.1	6.9	44.5	21.4	34.0	47.0	32.4	71.8	84.1	68.5	81.2	93.3	0.0
W	Num	10	334	272	4	21	22	2	16	193	8	10	5	5	0
	Flex	.02	.00	.00	.56	.21	.41	.56	.15	1.23	.83	1.14	1.38	1.31	0.00
	Rigid	.05	.00	.00	.85	.21	.75	1.48	.18	2.36	2.05	1.10	2.27	2.50	0.00
	GVW	13.2	2.8	4.8	37.9	17.3	32.6	60.3	25.4	68.6	83.6	57.0	77.0	90.7	0.0
E Lane1	Num	2	466	180	3	20	8	1	18	197	6	7	4	5	0
	Flex	.01	.00	.01	1.03	.49	.40	.22	.46	1.48	.88	3.02	2.28	1.80	0.00
	Rigid	.03	.00	.01	1.63	.49	.74	.62	.54	2.84	2.24	3.08	2.72	3.12	0.00
	GVW	10.7	6.1	6.9	44.5	21.4	34.0	47.0	32.4	71.8	84.1	68.5	81.2	93.3	0.0
W Lane1	Num	10	334	272	4	21	22	2	16	193	8	10	5	5	0
	Flex	.02	.00	.00	.56	.21	.41	.56	.15	1.23	.83	1.14	1.38	1.31	0.00
	Rigid	.05	.00	.00	.85	.21	.75	1.48	.18	2.36	2.05	1.10	2.27	2.50	0.00
	GVW	13.2	2.8	4.8	37.9	17.3	32.6	60.3	25.4	68.6	83.6	57.0	77.0	90.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9