

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2024

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	2,002	113	3	14	8	1	10	148	5	7	3	3	0
	Flex	2.73	.00	.01	.34	.42	.70	.28	.82	1.69	1.04	3.57	3.52	2.44	0.00
	Rigid	6.98	.01	.01	.44	.42	1.34	.63	1.10	3.36	2.71	3.64	4.34	5.54	0.00
	GVW	22.7	3.7	7.4	26.0	21.0	37.5	47.6	37.9	72.2	89.4	74.9	89.2	118.8	0.0
E	Num	2	1,155	3	0	0	0	0	0	1	0	0	0	0	0
	Flex	.00	.00	.00	0.00	0.00	0.00	0.00	0.00	.00	0.00	0.00	0.00	0.00	0.00
	Rigid	.00	.00	.00	0.00	0.00	0.00	0.00	0.00	.00	0.00	0.00	0.00	0.00	0.00
	GVW	2.8	1.4	1.7	0.0	0.0	0.0	0.0	0.0	10.3	0.0	0.0	0.0	0.0	0.0
W	Num	2	847	112	3	14	8	1	10	148	5	7	3	3	0
	Flex	2.73	.01	.01	.34	.42	.70	.28	.82	1.69	1.04	3.57	3.52	2.44	0.00
	Rigid	6.98	.01	.01	.44	.42	1.34	.63	1.10	3.36	2.71	3.64	4.34	5.54	0.00
	GVW	23.5	6.8	7.4	26.0	21.0	37.5	47.6	37.9	72.3	89.4	74.9	89.2	118.8	0.0
E Lane1	Num	2	1,155	3	0	0	0	0	0	1	0	0	0	0	0
	Flex	.00	.00	.00	0.00	0.00	0.00	0.00	0.00	.00	0.00	0.00	0.00	0.00	0.00
	Rigid	.00	.00	.00	0.00	0.00	0.00	0.00	0.00	.00	0.00	0.00	0.00	0.00	0.00
	GVW	2.8	1.4	1.7	0.0	0.0	0.0	0.0	0.0	10.3	0.0	0.0	0.0	0.0	0.0
W Lane1	Num	2	847	112	3	14	8	1	10	148	5	7	3	3	0
	Flex	2.73	.01	.01	.34	.42	.70	.28	.82	1.69	1.04	3.57	3.52	2.44	0.00
	Rigid	6.98	.01	.01	.44	.42	1.34	.63	1.10	3.36	2.71	3.64	4.34	5.54	0.00
	GVW	23.5	6.8	7.4	26.0	21.0	37.5	47.6	37.9	72.3	89.4	74.9	89.2	118.8	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2024

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9