

Idaho Transportation Department

Monthly WIM Distribution for Jul-2024

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	14	964	764	10	75	21	0	53	548	64	2	18	40	0
	Flex	.03	.00	.00	1.12	.51	.36	0.00	.27	1.13	.90	1.31	1.43	2.57	0.00
	Rigid	.07	.00	.00	1.33	.51	.63	0.00	.32	2.12	2.18	1.26	1.67	3.10	0.00
	GVW	5.0	3.6	5.9	42.3	21.6	33.5	0.0	27.8	66.7	83.1	60.1	75.5	97.8	0.0
E	Num	9	504	391	8	38	7	0	31	269	41	1	8	19	0
	Flex	.05	.00	.00	1.24	.72	.30	0.00	.30	1.34	1.08	1.87	1.74	3.32	0.00
	Rigid	.11	.00	.00	1.41	.73	.53	0.00	.34	2.52	2.68	1.81	2.01	3.96	0.00
	GVW	7.4	2.9	5.3	42.5	23.4	31.4	0.0	25.2	68.8	88.2	66.2	77.5	102.1	0.0
W	Num	5	460	373	2	37	14	0	22	279	23	1	10	21	0
	Flex	.00	.00	.00	.65	.29	.39	0.00	.23	.94	.58	.74	1.18	1.89	0.00
	Rigid	.00	.00	.00	.99	.28	.68	0.00	.28	1.74	1.30	.70	1.39	2.33	0.00
	GVW	.7	4.4	6.5	41.7	19.8	34.6	0.0	31.6	64.6	74.0	54.0	73.9	93.9	0.0
E Lane1	Num	9	504	391	8	38	7	0	31	269	41	1	8	19	0
	Flex	.05	.00	.00	1.24	.72	.30	0.00	.30	1.34	1.08	1.87	1.74	3.32	0.00
	Rigid	.11	.00	.00	1.41	.73	.53	0.00	.34	2.52	2.68	1.81	2.01	3.96	0.00
	GVW	7.4	2.9	5.3	42.5	23.4	31.4	0.0	25.2	68.8	88.2	66.2	77.5	102.1	0.0
W Lane1	Num	5	460	373	2	37	14	0	22	279	23	1	10	21	0
	Flex	.00	.00	.00	.65	.29	.39	0.00	.23	.94	.58	.74	1.18	1.89	0.00
	Rigid	.00	.00	.00	.99	.28	.68	0.00	.28	1.74	1.30	.70	1.39	2.33	0.00
	GVW	.7	4.4	6.5	41.7	19.8	34.6	0.0	31.6	64.6	74.0	54.0	73.9	93.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2024

Site names: 00138

County: Owyhee

Funct Class: R Principal Arterial - Other

Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4

Daily Factor Grp: 4

Axle Factor Grp: All_Class_Sites

Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9