

Idaho Transportation Department

Monthly WIM Distribution for Aug-2024

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	15	1,079	821	7	66	21	2	49	457	43	4	14	37	0
	Flex	.04	.00	.00	.67	.47	.37	.41	.21	1.11	.99	1.64	1.38	1.95	0.00
	Rigid	.08	.00	.00	.92	.47	.60	1.02	.26	2.07	2.38	1.60	1.65	2.68	0.00
	GVW	3.4	3.4	5.7	36.6	21.3	31.5	48.8	26.6	66.5	84.6	62.7	73.6	90.9	0.0
E	Num	8	560	412	3	34	10	1	26	215	31	2	7	19	0
	Flex	.06	.00	.00	.67	.54	.42	.54	.19	1.27	1.14	2.09	1.57	2.55	0.00
	Rigid	.13	.00	.00	.90	.55	.68	1.41	.24	2.30	2.74	2.09	1.88	3.51	0.00
	GVW	4.7	2.8	4.8	33.7	21.1	30.9	46.6	23.7	67.7	88.1	63.4	74.6	99.5	0.0
W	Num	7	520	409	3	32	11	1	23	243	12	3	6	18	0
	Flex	.01	.00	.00	.59	.39	.33	.31	.23	.98	.63	1.24	1.17	1.21	0.00
	Rigid	.01	.00	.00	.83	.38	.54	.76	.28	1.87	1.50	1.18	1.40	1.68	0.00
	GVW	1.3	4.1	6.5	38.0	21.6	32.4	52.0	29.8	65.5	75.5	60.0	72.4	80.1	0.0
E Lane1	Num	8	560	412	3	34	10	1	26	215	31	2	7	19	0
	Flex	.06	.00	.00	.67	.54	.42	.54	.19	1.27	1.14	2.09	1.57	2.55	0.00
	Rigid	.13	.00	.00	.90	.55	.68	1.41	.24	2.30	2.74	2.09	1.88	3.51	0.00
	GVW	4.7	2.8	4.8	33.7	21.1	30.9	46.6	23.7	67.7	88.1	63.4	74.6	99.5	0.0
W Lane1	Num	7	520	409	3	32	11	1	23	243	12	3	6	18	0
	Flex	.01	.00	.00	.59	.39	.33	.31	.23	.98	.63	1.24	1.17	1.21	0.00
	Rigid	.01	.00	.00	.83	.38	.54	.76	.28	1.87	1.50	1.18	1.40	1.68	0.00
	GVW	1.3	4.1	6.5	38.0	21.6	32.4	52.0	29.8	65.5	75.5	60.0	72.4	80.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Aug-2024

Site names: 00138
County: Owyhee
Funct Class: R Principal Arterial - Other
Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
Daily Factor Grp: 4
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 3

		UNCLS
--	--	-------

Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9