

Idaho Transportation Department

Monthly WIM Distribution for Nov-2024

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	733	692	5	41	13	1	36	457	34	16	10	20	0
	Flex	.47	.00	.00	1.02	.42	.49	1.39	.24	1.38	1.25	2.15	1.31	2.26	0.00
	Rigid	1.02	.00	.00	1.51	.42	.83	2.20	.29	2.61	3.12	2.15	1.53	3.34	0.00
	GVW	20.2	3.3	5.5	45.1	19.8	32.4	65.7	27.5	68.9	85.0	63.0	70.8	92.6	0.0
E	Num	2	356	335	2	20	7	2	19	234	19	8	5	10	0
	Flex	.44	.00	.00	1.14	.37	.46	.55	.22	1.19	1.56	1.70	.96	3.23	0.00
	Rigid	.96	.00	.00	1.50	.37	.75	1.46	.25	2.14	4.00	1.69	1.12	4.75	0.00
	GVW	20.0	2.5	4.4	42.8	18.0	30.3	51.0	24.7	65.4	90.7	57.4	67.1	103.9	0.0
W	Num	1	377	358	3	21	6	1	18	223	15	9	5	10	0
	Flex	.25	.00	.00	.97	.47	.52	1.81	.25	1.58	.85	2.81	1.60	1.30	0.00
	Rigid	.53	.00	.00	1.55	.47	.91	2.50	.31	3.12	2.02	2.83	1.88	2.13	0.00
	GVW	17.1	4.2	6.5	47.4	21.5	34.6	74.1	30.5	72.6	78.0	70.1	73.8	82.9	0.0
E Lane1	Num	2	356	335	2	20	7	2	19	234	19	8	5	10	0
	Flex	.44	.00	.00	1.14	.37	.46	.55	.22	1.19	1.56	1.70	.96	3.23	0.00
	Rigid	.96	.00	.00	1.50	.37	.75	1.46	.25	2.14	4.00	1.69	1.12	4.75	0.00
	GVW	20.0	2.5	4.4	42.8	18.0	30.3	51.0	24.7	65.4	90.7	57.4	67.1	103.9	0.0
W Lane1	Num	1	377	358	3	21	6	1	18	223	15	9	5	10	0
	Flex	.25	.00	.00	.97	.47	.52	1.81	.25	1.58	.85	2.81	1.60	1.30	0.00
	Rigid	.53	.00	.00	1.55	.47	.91	2.50	.31	3.12	2.02	2.83	1.88	2.13	0.00
	GVW	17.1	4.2	6.5	47.4	21.5	34.6	74.1	30.5	72.6	78.0	70.1	73.8	82.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2024

Site names: 00138
County: Owyhee
Funct Class: R Principal Arterial - Other
Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
Daily Factor Grp: 4
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 3

		UNCLS
--	--	-------

Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9