

Idaho Transportation Department

Monthly WIM Distribution for Dec-2024

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	670	579	4	33	16	4	29	415	24	12	11	15	0
	Flex	.85	.00	.00	1.05	.43	.50	2.18	.34	1.32	1.09	2.36	1.41	2.15	0.00
	Rigid	1.86	.00	.00	1.41	.43	.85	3.76	.40	2.54	2.72	2.36	1.88	3.19	0.00
	GVW	24.0	3.4	5.3	39.9	19.7	33.4	99.4	29.5	68.5	88.2	67.1	75.0	95.4	0.0
E	Num	1	332	290	2	17	7	1	15	220	9	6	5	7	0
	Flex	.28	.00	.00	1.04	.42	.48	1.48	.33	1.13	.96	3.12	1.05	2.86	0.00
	Rigid	.59	.00	.00	1.47	.42	.75	5.75	.38	2.10	2.33	3.19	1.20	3.86	0.00
	GVW	11.5	2.5	4.2	42.9	18.5	31.3	85.4	26.3	65.2	81.1	70.9	66.9	93.5	0.0
W	Num	1	338	289	2	16	9	4	13	196	16	6	6	9	0
	Flex	1.15	.01	.00	1.10	.44	.53	2.22	.34	1.52	1.12	1.80	1.90	1.56	0.00
	Rigid	2.52	.01	.00	1.47	.43	.95	3.58	.43	3.00	2.78	1.76	2.61	2.57	0.00
	GVW	30.5	4.3	6.4	39.7	21.0	35.7	99.5	33.1	72.1	90.5	64.3	83.1	94.0	0.0
E Lane1	Num	1	332	290	2	17	7	1	15	220	9	6	5	7	0
	Flex	.28	.00	.00	1.04	.42	.48	1.48	.33	1.13	.96	3.12	1.05	2.86	0.00
	Rigid	.59	.00	.00	1.47	.42	.75	5.75	.38	2.10	2.33	3.19	1.20	3.86	0.00
	GVW	11.5	2.5	4.2	42.9	18.5	31.3	85.4	26.3	65.2	81.1	70.9	66.9	93.5	0.0
W Lane1	Num	1	338	289	2	16	9	4	13	196	16	6	6	9	0
	Flex	1.15	.01	.00	1.10	.44	.53	2.22	.34	1.52	1.12	1.80	1.90	1.56	0.00
	Rigid	2.52	.01	.00	1.47	.43	.95	3.58	.43	3.00	2.78	1.76	2.61	2.57	0.00
	GVW	30.5	4.3	6.4	39.7	21.0	35.7	99.5	33.1	72.1	90.5	64.3	83.1	94.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2024

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9