

Idaho Transportation Department

Monthly WIM Distribution for Apr-2025

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp:
 Daily Factor Grp:
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	7	837	711	6	51	17	2	49	486	32	6	13	18	0
	Flex	.06	.00	.00	.87	.44	.57	.73	.22	1.31	.98	1.82	1.10	2.06	0.00
	Rigid	.12	.00	.00	1.22	.44	1.01	1.33	.27	2.41	2.37	1.81	1.35	2.68	0.00
	GVW	4.0	3.4	5.6	41.3	20.5	35.7	57.3	26.4	68.1	82.8	62.7	69.3	91.5	0.0
E	Num	4	422	356	3	28	8	2	25	243	20	3	7	9	0
	Flex	.05	.00	.00	.85	.48	.48	.42	.19	1.41	1.08	2.84	1.08	2.38	0.00
	Rigid	.11	.00	.00	1.19	.48	.79	1.24	.24	2.51	2.58	2.89	1.32	2.97	0.00
	GVW	4.9	2.6	4.8	42.2	20.2	32.9	62.3	23.7	68.4	83.1	69.6	68.7	89.7	0.0
W	Num	3	414	355	3	23	9	2	25	243	13	4	6	8	0
	Flex	.05	.00	.00	.85	.38	.61	.83	.25	1.22	.90	1.18	1.09	1.53	0.00
	Rigid	.11	.00	.00	1.28	.38	1.10	1.31	.29	2.33	2.25	1.13	1.34	2.21	0.00
	GVW	1.9	4.1	6.5	43.1	20.8	38.0	56.7	29.2	67.9	83.9	58.0	69.7	92.6	0.0
E Lane1	Num	4	422	356	3	28	8	2	25	243	20	3	7	9	0
	Flex	.05	.00	.00	.85	.48	.48	.42	.19	1.41	1.08	2.84	1.08	2.38	0.00
	Rigid	.11	.00	.00	1.19	.48	.79	1.24	.24	2.51	2.58	2.89	1.32	2.97	0.00
	GVW	4.9	2.6	4.8	42.2	20.2	32.9	62.3	23.7	68.4	83.1	69.6	68.7	89.7	0.0
W Lane1	Num	3	414	355	3	23	9	2	25	243	13	4	6	8	0
	Flex	.05	.00	.00	.85	.38	.61	.83	.25	1.22	.90	1.18	1.09	1.53	0.00
	Rigid	.11	.00	.00	1.28	.38	1.10	1.31	.29	2.33	2.25	1.13	1.34	2.21	0.00
	GVW	1.9	4.1	6.5	43.1	20.8	38.0	56.7	29.2	67.9	83.9	58.0	69.7	92.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2025

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp:
 Daily Factor Grp:
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9