

Idaho Transportation Department

Monthly WIM Distribution for Jun-2025

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp:
 Daily Factor Grp:
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	17	1,170	855	6	70	21	2	57	491	48	5	12	21	0
	Flex	.03	.00	.00	.73	.43	.42	.39	.18	1.09	.88	1.51	1.20	1.89	0.00
	Rigid	.07	.00	.00	1.02	.43	.73	.75	.21	2.02	2.10	1.47	1.43	2.48	0.00
	GVW	3.4	3.4	5.6	39.6	20.9	33.3	46.2	25.4	66.4	83.2	59.6	70.9	94.4	0.0
E	Num	10	596	436	3	37	8	1	29	230	37	2	7	13	0
	Flex	.07	.00	.00	.83	.49	.35	.56	.14	1.26	.94	1.85	1.12	1.99	0.00
	Rigid	.15	.00	.00	1.16	.49	.55	1.12	.17	2.30	2.26	1.82	1.38	2.57	0.00
	GVW	5.9	2.7	4.8	41.0	20.7	30.8	50.8	22.4	68.4	85.0	60.0	70.2	94.7	0.0
W	Num	8	574	419	4	33	13	2	28	261	10	3	5	8	0
	Flex	.01	.00	.00	.66	.37	.46	.16	.21	.94	.64	1.26	1.16	1.55	0.00
	Rigid	.02	.00	.00	.93	.36	.84	.35	.25	1.77	1.51	1.20	1.34	2.09	0.00
	GVW	1.3	4.2	6.5	39.6	21.1	34.8	40.9	28.7	64.6	76.5	60.4	70.2	90.6	0.0
E Lane1	Num	10	596	436	3	37	8	1	29	230	37	2	7	13	0
	Flex	.07	.00	.00	.83	.49	.35	.56	.14	1.26	.94	1.85	1.12	1.99	0.00
	Rigid	.15	.00	.00	1.16	.49	.55	1.12	.17	2.30	2.26	1.82	1.38	2.57	0.00
	GVW	5.9	2.7	4.8	41.0	20.7	30.8	50.8	22.4	68.4	85.0	60.0	70.2	94.7	0.0
W Lane1	Num	8	574	419	4	33	13	2	28	261	10	3	5	8	0
	Flex	.01	.00	.00	.66	.37	.46	.16	.21	.94	.64	1.26	1.16	1.55	0.00
	Rigid	.02	.00	.00	.93	.36	.84	.35	.25	1.77	1.51	1.20	1.34	2.09	0.00
	GVW	1.3	4.2	6.5	39.6	21.1	34.8	40.9	28.7	64.6	76.5	60.4	70.2	90.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2025

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp:
 Daily Factor Grp:
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9