

Idaho Transportation Department

Monthly WIM Distribution for Dec-2018

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,002	857	11	56	21	1	24	82	94	2	1	52	0
	Flex	.00	.00	.00	.26	.11	.39	.22	.21	.22	.35	.40	.29	.30	0.00
	Rigid	.00	.00	.00	.34	.10	.52	.43	.21	.32	.76	.37	.29	.58	0.00
	GVW	3.2	3.4	5.9	25.0	15.2	29.7	36.8	28.6	36.4	68.2	42.4	38.3	57.5	0.0
E	Num	1	483	416	6	29	10	1	16	48	29	1	1	42	0
	Flex	.00	.00	.00	.29	.12	.57	.07	.23	.23	.42	.48	.37	.28	0.00
	Rigid	.00	.00	.00	.38	.12	.81	.26	.23	.34	.95	.45	.42	.56	0.00
	GVW	3.0	3.3	5.7	26.0	15.6	34.3	30.9	29.5	36.8	71.7	47.1	55.3	58.4	0.0
W	Num	1	519	441	6	28	12	1	9	34	64	1	1	10	0
	Flex	.00	.00	.00	.21	.09	.26	.35	.14	.19	.32	.31	.27	.45	0.00
	Rigid	.00	.00	.00	.23	.09	.32	.58	.16	.28	.68	.29	.27	.78	0.00
	GVW	2.5	3.6	6.0	21.5	14.8	26.3	43.1	25.4	35.7	66.5	39.5	37.1	56.8	0.0
E Lane1	Num	1	483	416	6	29	10	1	16	48	29	1	1	42	0
	Flex	.00	.00	.00	.29	.12	.57	.07	.23	.23	.42	.48	.37	.28	0.00
	Rigid	.00	.00	.00	.38	.12	.81	.26	.23	.34	.95	.45	.42	.56	0.00
	GVW	3.0	3.3	5.7	26.0	15.6	34.3	30.9	29.5	36.8	71.7	47.1	55.3	58.4	0.0
W Lane1	Num	1	519	441	6	28	12	1	9	34	64	1	1	10	0
	Flex	.00	.00	.00	.21	.09	.26	.35	.14	.19	.32	.31	.27	.45	0.00
	Rigid	.00	.00	.00	.23	.09	.32	.58	.16	.28	.68	.29	.27	.78	0.00
	GVW	2.5	3.6	6.0	21.5	14.8	26.3	43.1	25.4	35.7	66.5	39.5	37.1	56.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2018

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9