

Idaho Transportation Department

Monthly WIM Distribution for Oct-2017

Site names: 00156
 County: Butte
 Funct Class: R Minor Arterial - Other
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	252	262	2	8	4	2	8	56	27	2	1	27	0
	Flex	.00	.00	.00	1.17	1.57	.65	1.15	.48	1.42	1.00	.29	1.18	1.95	0.00
	Rigid	.00	.00	.00	1.59	1.76	.92	1.30	.61	2.41	2.29	.32	1.65	2.77	0.00
	GVW	2.2	3.9	4.4	34.4	23.9	21.8	29.8	21.8	56.0	72.3	24.8	49.4	67.8	0.0
E	Num	2	127	126	1	3	4	1	4	25	10	2	1	13	0
	Flex	.00	.00	.00	.79	.81	.28	.42	.18	.69	.56	.24	.35	.42	0.00
	Rigid	.00	.00	.00	1.19	.87	.48	.43	.22	1.14	1.17	.24	.37	.61	0.00
	GVW	1.7	3.8	4.5	36.0	22.3	17.5	29.1	20.3	50.7	58.1	24.6	44.8	44.1	0.0
W	Num	1	125	136	2	5	2	2	5	31	17	1	1	14	0
	Flex	.00	.00	.00	1.67	1.97	1.08	1.26	.68	2.00	1.42	.25	6.27	3.16	0.00
	Rigid	.00	.00	.00	2.24	2.22	1.46	1.43	.85	3.43	3.31	.28	8.08	4.41	0.00
	GVW	3.3	4.0	4.2	35.5	25.1	26.7	30.3	22.4	60.3	84.7	23.6	53.6	86.4	0.0
E Lane1	Num	2	127	126	1	3	4	1	4	25	10	2	1	13	0
	Flex	.00	.00	.00	.79	.81	.28	.42	.18	.69	.56	.24	.35	.42	0.00
	Rigid	.00	.00	.00	1.19	.87	.48	.43	.22	1.14	1.17	.24	.37	.61	0.00
	GVW	1.7	3.8	4.5	36.0	22.3	17.5	29.1	20.3	50.7	58.1	24.6	44.8	44.1	0.0
W Lane1	Num	1	125	136	2	5	2	2	5	31	17	1	1	14	0
	Flex	.00	.00	.00	1.67	1.97	1.08	1.26	.68	2.00	1.42	.25	6.27	3.16	0.00
	Rigid	.00	.00	.00	2.24	2.22	1.46	1.43	.85	3.43	3.31	.28	8.08	4.41	0.00
	GVW	3.3	4.0	4.2	35.5	25.1	26.7	30.3	22.4	60.3	84.7	23.6	53.6	86.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2017

Site names: 00156
 County: Butte
 Funct Class: R Minor Arterial - Other
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9