

Idaho Transportation Department

Monthly WIM Distribution for Jan-2023

Site names: 00156
 County: Butte
 Funct Class: R Minor Arterial - Other
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 4

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	175	116	1	9	12	2	9	30	11	1	3	23	0
	Flex	.01	.01	.00	.38	.30	.44	.38	.15	.94	.62	2.61	1.62	2.14	0.00
	Rigid	.02	.01	.00	.55	.30	.78	.94	.19	1.71	1.53	3.46	2.28	2.94	0.00
	GVW	9.0	3.3	4.2	32.2	17.3	32.1	48.6	23.1	58.5	75.7	60.4	63.6	85.4	0.0
E	Num	2	91	56	1	4	7	1	6	12	5	1	2	10	0
	Flex	.01	.00	.00	.21	.18	.33	.12	.12	.61	.39	.28	.18	.80	0.00
	Rigid	.02	.00	.00	.31	.18	.60	.28	.14	1.13	.89	.27	.24	1.06	0.00
	GVW	9.7	3.3	4.0	27.8	15.7	30.9	31.5	22.7	54.3	63.1	36.8	44.6	64.3	0.0
W	Num	2	85	60	1	4	5	2	3	17	6	1	2	13	0
	Flex	.01	.01	.00	.60	.41	.59	.44	.21	1.14	.89	3.44	3.94	3.24	0.00
	Rigid	.02	.01	.00	.85	.42	1.04	1.09	.26	2.06	2.22	4.69	5.49	4.47	0.00
	GVW	9.1	3.2	4.4	37.1	18.9	34.3	51.7	24.2	61.1	85.1	73.7	95.0	102.2	0.0
E Lane1	Num	2	91	56	1	4	7	1	6	12	5	1	2	10	0
	Flex	.01	.00	.00	.21	.18	.33	.12	.12	.61	.39	.28	.18	.80	0.00
	Rigid	.02	.00	.00	.31	.18	.60	.28	.14	1.13	.89	.27	.24	1.06	0.00
	GVW	9.7	3.3	4.0	27.8	15.7	30.9	31.5	22.7	54.3	63.1	36.8	44.6	64.3	0.0
W Lane1	Num	2	85	60	1	4	5	2	3	17	6	1	2	13	0
	Flex	.01	.01	.00	.60	.41	.59	.44	.21	1.14	.89	3.44	3.94	3.24	0.00
	Rigid	.02	.01	.00	.85	.42	1.04	1.09	.26	2.06	2.22	4.69	5.49	4.47	0.00
	GVW	9.1	3.2	4.4	37.1	18.9	34.3	51.7	24.2	61.1	85.1	73.7	95.0	102.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2023

Site names: 00156
 County: Butte
 Funct Class: R Minor Arterial - Other
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 4

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9