

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2017

Site names: 00169  
 County: Payette  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	7	2,097	1,448	17	153	29	2	13	296	51	1	2	21	0
	Flex	.00	.00	.00	.51	.12	.39	.72	.30	.99	.60	1.47	.59	.85	0.00
	Rigid	.00	.00	.00	.56	.12	.64	1.86	.35	1.73	1.33	1.45	.61	1.92	0.00
	GVW	3.4	3.8	6.3	24.4	15.8	28.5	58.9	29.3	58.6	69.7	55.4	55.2	82.3	0.0
N	Num	4	1,089	713	9	74	15	3	7	138	27	1	1	10	0
	Flex	.00	.00	.00	.49	.13	.33	.68	.36	.84	.48	1.50	.83	.47	0.00
	Rigid	.00	.00	.00	.55	.13	.58	1.51	.41	1.51	1.07	1.47	.86	1.16	0.00
	GVW	3.5	3.9	6.4	24.5	16.2	27.1	56.7	29.9	56.5	65.3	57.1	63.6	71.2	0.0
S	Num	3	1,008	735	9	79	16	2	6	159	23	1	1	11	0
	Flex	.00	.00	.00	.53	.12	.52	.72	.24	1.11	.73	1.66	.30	1.17	0.00
	Rigid	.00	.00	.00	.57	.12	.80	1.87	.28	1.90	1.61	1.65	.30	2.54	0.00
	GVW	3.6	3.7	6.2	24.3	15.5	31.7	57.2	26.8	60.3	74.4	54.0	43.5	91.0	0.0
N Lane1	Num	4	1,089	713	9	74	15	3	7	138	27	1	1	10	0
	Flex	.00	.00	.00	.49	.13	.33	.68	.36	.84	.48	1.50	.83	.47	0.00
	Rigid	.00	.00	.00	.55	.13	.58	1.51	.41	1.51	1.07	1.47	.86	1.16	0.00
	GVW	3.5	3.9	6.4	24.5	16.2	27.1	56.7	29.9	56.5	65.3	57.1	63.6	71.2	0.0
S Lane1	Num	3	1,008	735	9	79	16	2	6	159	23	1	1	11	0
	Flex	.00	.00	.00	.53	.12	.52	.72	.24	1.11	.73	1.66	.30	1.17	0.00
	Rigid	.00	.00	.00	.57	.12	.80	1.87	.28	1.90	1.61	1.65	.30	2.54	0.00
	GVW	3.6	3.7	6.2	24.3	15.5	31.7	57.2	26.8	60.3	74.4	54.0	43.5	91.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2017

Site names: 00169  
 County: Payette  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9