

Idaho Transportation Department

Monthly WIM Distribution for Apr-2017

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	9	2,204	1,549	23	170	55	6	15	224	36	1	2	20	0
	Flex	.00	.00	.00	.55	.10	.39	.65	.46	.97	.57	1.11	.68	.85	0.00
	Rigid	.00	.00	.00	.58	.10	.64	1.28	.56	1.69	1.26	1.09	.70	1.89	0.00
	GVW	2.8	3.8	6.2	24.0	15.8	29.3	50.7	31.7	57.6	66.3	50.6	54.1	82.6	0.0
N	Num	5	1,140	770	11	81	33	4	9	104	18	1	1	8	0
	Flex	.00	.00	.00	.48	.09	.26	.52	.34	.80	.47	1.85	1.34	.53	0.00
	Rigid	.00	.00	.00	.50	.10	.44	1.18	.39	1.42	1.04	1.81	1.44	1.32	0.00
	GVW	2.7	3.8	6.3	22.8	15.8	27.1	51.6	30.4	54.7	61.7	65.9	68.8	74.1	0.0
S	Num	4	1,063	779	12	88	22	3	7	120	18	1	1	12	0
	Flex	.00	.00	.00	.63	.10	.55	.65	.55	1.11	.65	.19	.33	1.04	0.00
	Rigid	.00	.00	.00	.68	.11	.88	1.26	.68	1.93	1.41	.18	.33	2.23	0.00
	GVW	2.8	3.7	6.1	25.2	15.8	31.9	49.4	32.5	60.3	69.6	32.9	42.8	88.2	0.0
N Lane1	Num	5	1,140	770	11	81	33	4	9	104	18	1	1	8	0
	Flex	.00	.00	.00	.48	.09	.26	.52	.34	.80	.47	1.85	1.34	.53	0.00
	Rigid	.00	.00	.00	.50	.10	.44	1.18	.39	1.42	1.04	1.81	1.44	1.32	0.00
	GVW	2.7	3.8	6.3	22.8	15.8	27.1	51.6	30.4	54.7	61.7	65.9	68.8	74.1	0.0
S Lane1	Num	4	1,063	779	12	88	22	3	7	120	18	1	1	12	0
	Flex	.00	.00	.00	.63	.10	.55	.65	.55	1.11	.65	.19	.33	1.04	0.00
	Rigid	.00	.00	.00	.68	.11	.88	1.26	.68	1.93	1.41	.18	.33	2.23	0.00
	GVW	2.8	3.7	6.1	25.2	15.8	31.9	49.4	32.5	60.3	69.6	32.9	42.8	88.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2017

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9