

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	11	2,146	1,608	20	158	41	5	16	100	18	1	1	11	0
	Flex	.00	.00	.00	.56	.10	.39	.45	.40	.87	.64	.39	.37	.58	0.00
	Rigid	.00	.00	.00	.60	.10	.64	1.09	.49	1.54	1.43	.37	.39	1.34	0.00
	GVW	2.9	3.7	6.2	22.8	16.0	29.8	47.3	30.4	54.5	64.6	38.4	46.2	73.5	0.0
N	Num	6	1,144	809	10	65	26	3	9	43	9	1	1	6	0
	Flex	.00	.00	.00	.41	.09	.27	.20	.28	.64	.38	.44	.53	.41	0.00
	Rigid	.00	.00	.00	.41	.09	.47	.57	.31	1.16	.83	.42	.55	.93	0.00
	GVW	2.5	3.7	6.2	21.2	15.5	29.5	43.0	28.6	51.1	55.3	41.9	53.5	66.8	0.0
S	Num	6	1,040	799	10	95	16	4	7	57	9	1	1	5	0
	Flex	.00	.00	.00	.79	.10	.59	.69	.62	1.04	.87	.08	.44	.84	0.00
	Rigid	.00	.00	.00	.85	.10	.91	1.53	.79	1.82	1.94	.08	.46	1.91	0.00
	GVW	3.2	3.6	6.1	24.9	15.9	30.7	51.1	32.8	57.0	72.2	27.4	41.4	81.5	0.0
N Lane1	Num	6	1,144	809	10	65	26	3	9	43	9	1	1	6	0
	Flex	.00	.00	.00	.41	.09	.27	.20	.28	.64	.38	.44	.53	.41	0.00
	Rigid	.00	.00	.00	.41	.09	.47	.57	.31	1.16	.83	.42	.55	.93	0.00
	GVW	2.5	3.7	6.2	21.2	15.5	29.5	43.0	28.6	51.1	55.3	41.9	53.5	66.8	0.0
S Lane1	Num	6	1,040	799	10	95	16	4	7	57	9	1	1	5	0
	Flex	.00	.00	.00	.79	.10	.59	.69	.62	1.04	.87	.08	.44	.84	0.00
	Rigid	.00	.00	.00	.85	.10	.91	1.53	.79	1.82	1.94	.08	.46	1.91	0.00
	GVW	3.2	3.6	6.1	24.9	15.9	30.7	51.1	32.8	57.0	72.2	27.4	41.4	81.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9