

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	9	2,416	1,802	32	101	195	12	11	152	77	1	1	25	0
	Flex	.00	.00	.00	.26	.14	.25	.14	.15	.39	.36	.14	.18	.32	0.00
	Rigid	.00	.00	.00	.30	.14	.44	.42	.16	.68	.76	.13	.18	.70	0.00
	GVW	3.2	3.5	5.8	21.2	16.3	27.2	42.1	24.6	45.1	55.9	31.8	38.2	65.0	0.0
N	Num	5	1,228	891	15	47	93	8	6	71	36	1	1	15	0
	Flex	.00	.00	.00	.23	.13	.22	.17	.15	.43	.41	.05	.29	.24	0.00
	Rigid	.00	.00	.00	.26	.13	.39	.43	.16	.75	.90	.05	.30	.64	0.00
	GVW	3.0	3.6	5.9	20.2	16.3	26.2	42.3	26.6	47.0	61.0	25.1	52.3	64.9	0.0
S	Num	3	1,187	912	17	54	102	5	6	82	40	1	1	10	0
	Flex	.00	.00	.00	.28	.15	.28	.12	.15	.36	.29	.17	.16	.39	0.00
	Rigid	.00	.00	.00	.31	.15	.47	.43	.17	.62	.60	.16	.16	.75	0.00
	GVW	4.1	3.4	5.8	21.5	16.3	28.0	41.7	23.6	43.5	50.3	34.0	36.2	63.3	0.0
N Lane1	Num	5	1,228	891	15	47	93	8	6	71	36	1	1	15	0
	Flex	.00	.00	.00	.23	.13	.22	.17	.15	.43	.41	.05	.29	.24	0.00
	Rigid	.00	.00	.00	.26	.13	.39	.43	.16	.75	.90	.05	.30	.64	0.00
	GVW	3.0	3.6	5.9	20.2	16.3	26.2	42.3	26.6	47.0	61.0	25.1	52.3	64.9	0.0
S Lane1	Num	3	1,187	912	17	54	102	5	6	82	40	1	1	10	0
	Flex	.00	.00	.00	.28	.15	.28	.12	.15	.36	.29	.17	.16	.39	0.00
	Rigid	.00	.00	.00	.31	.15	.47	.43	.17	.62	.60	.16	.16	.75	0.00
	GVW	4.1	3.4	5.8	21.5	16.3	28.0	41.7	23.6	43.5	50.3	34.0	36.2	63.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9