

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2022

Site names: 00169  
 County: Payette  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	11	3,035	1,632	4	71	41	8	76	256	42	2	3	24	0
	Flex	.02	.00	.00	.43	.21	.27	.35	.13	.71	.43	1.89	.77	1.11	0.00
	Rigid	.03	.00	.00	.58	.20	.43	.86	.16	1.29	1.05	2.01	1.32	1.67	0.00
	GVW	2.8	2.6	4.6	35.5	17.2	29.8	55.1	22.8	58.1	68.7	59.3	66.1	76.2	0.0
N	Num	6	1,529	816	2	37	22	5	38	129	21	1	2	13	0
	Flex	.00	.00	.00	.41	.17	.26	.29	.13	.55	.36	.73	.42	.47	0.00
	Rigid	.00	.00	.00	.57	.16	.42	.60	.15	.96	.86	1.86	.63	.74	0.00
	GVW	1.8	2.8	4.9	38.5	17.4	30.6	49.4	24.0	56.9	67.6	73.3	56.5	63.6	0.0
S	Num	5	1,506	817	2	35	20	4	38	128	21	2	2	12	0
	Flex	.03	.00	.00	.55	.25	.28	.40	.13	.87	.49	2.35	.95	1.88	0.00
	Rigid	.07	.00	.00	.74	.24	.45	1.05	.17	1.63	1.21	2.37	1.73	2.77	0.00
	GVW	3.7	2.3	4.3	35.3	17.0	28.6	58.9	21.7	59.2	69.5	60.7	69.6	90.3	0.0
N Lane1	Num	6	1,529	816	2	37	22	5	38	129	21	1	2	13	0
	Flex	.00	.00	.00	.41	.17	.26	.29	.13	.55	.36	.73	.42	.47	0.00
	Rigid	.00	.00	.00	.57	.16	.42	.60	.15	.96	.86	1.86	.63	.74	0.00
	GVW	1.8	2.8	4.9	38.5	17.4	30.6	49.4	24.0	56.9	67.6	73.3	56.5	63.6	0.0
S Lane1	Num	5	1,506	817	2	35	20	4	38	128	21	2	2	12	0
	Flex	.03	.00	.00	.55	.25	.28	.40	.13	.87	.49	2.35	.95	1.88	0.00
	Rigid	.07	.00	.00	.74	.24	.45	1.05	.17	1.63	1.21	2.37	1.73	2.77	0.00
	GVW	3.7	2.3	4.3	35.3	17.0	28.6	58.9	21.7	59.2	69.5	60.7	69.6	90.3	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2022

Site names: 00169  
 County: Payette  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9