

Idaho Transportation Department

Monthly WIM Distribution for Aug-2023

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	12	3,112	1,864	9	99	106	10	75	259	64	4	2	25	0
	Flex	.02	.00	.00	.57	.22	.39	.26	.17	.95	.60	2.18	1.37	1.31	0.00
	Rigid	.05	.00	.00	.72	.21	.69	.75	.21	1.76	1.49	2.25	2.12	2.24	0.00
	GVW	10.2	2.5	4.5	27.6	16.7	31.7	48.2	23.4	60.6	76.8	56.3	71.8	84.9	0.0
N	Num	6	1,576	937	4	50	53	7	37	126	33	2	2	15	0
	Flex	.02	.00	.00	.29	.18	.37	.27	.17	.78	.59	.24	1.24	.43	0.00
	Rigid	.04	.00	.00	.33	.18	.65	.72	.20	1.38	1.45	.23	1.56	.85	0.00
	GVW	10.4	2.7	4.7	22.5	16.7	32.3	48.6	24.2	59.8	78.5	38.6	69.6	71.7	0.0
S	Num	6	1,536	927	5	49	53	5	38	132	31	2	2	10	0
	Flex	.02	.00	.00	.76	.25	.42	.25	.18	1.11	.60	3.84	1.48	2.30	0.00
	Rigid	.05	.00	.00	.97	.25	.75	.78	.21	2.11	1.53	4.00	2.71	3.78	0.00
	GVW	10.3	2.3	4.2	29.5	16.7	31.2	47.7	22.6	61.3	74.7	70.1	73.4	98.5	0.0
N Lane1	Num	6	1,576	937	4	50	53	7	37	126	33	2	2	15	0
	Flex	.02	.00	.00	.29	.18	.37	.27	.17	.78	.59	.24	1.24	.43	0.00
	Rigid	.04	.00	.00	.33	.18	.65	.72	.20	1.38	1.45	.23	1.56	.85	0.00
	GVW	10.4	2.7	4.7	22.5	16.7	32.3	48.6	24.2	59.8	78.5	38.6	69.6	71.7	0.0
S Lane1	Num	6	1,536	927	5	49	53	5	38	132	31	2	2	10	0
	Flex	.02	.00	.00	.76	.25	.42	.25	.18	1.11	.60	3.84	1.48	2.30	0.00
	Rigid	.05	.00	.00	.97	.25	.75	.78	.21	2.11	1.53	4.00	2.71	3.78	0.00
	GVW	10.3	2.3	4.2	29.5	16.7	31.2	47.7	22.6	61.3	74.7	70.1	73.4	98.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Aug-2023

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9