

Idaho Transportation Department

Monthly WIM Distribution for Oct-2023

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	17	2,991	1,828	14	103	115	7	69	309	93	2	4	31	0
	Flex	.05	.00	.00	.75	.30	.43	.34	.20	1.10	.71	1.52	1.15	1.64	0.00
	Rigid	.11	.00	.00	.90	.30	.78	.99	.23	2.06	1.82	1.54	1.93	2.67	0.00
	GVW	11.5	2.5	4.5	28.2	17.8	33.3	53.0	24.3	62.8	79.2	45.9	66.1	86.5	0.0
N	Num	9	1,540	924	6	53	59	4	34	151	51	3	2	17	0
	Flex	.02	.00	.00	.42	.24	.39	.33	.23	1.05	.64	.62	.48	1.26	0.00
	Rigid	.05	.00	.00	.50	.23	.69	.91	.27	1.93	1.65	.61	.72	2.19	0.00
	GVW	11.2	2.7	4.8	24.1	17.3	32.6	50.0	25.3	62.3	78.3	34.4	56.5	80.0	0.0
S	Num	9	1,451	905	7	50	55	3	35	159	42	1	3	15	0
	Flex	.10	.00	.00	1.02	.36	.47	.34	.17	1.15	.77	1.83	1.75	1.96	0.00
	Rigid	.22	.00	.00	1.22	.36	.86	1.17	.19	2.19	1.94	1.88	3.03	3.03	0.00
	GVW	12.2	2.3	4.3	31.4	18.3	33.9	55.9	23.3	63.4	78.7	48.2	71.0	92.5	0.0
N Lane1	Num	9	1,540	924	6	53	59	4	34	151	51	3	2	17	0
	Flex	.02	.00	.00	.42	.24	.39	.33	.23	1.05	.64	.62	.48	1.26	0.00
	Rigid	.05	.00	.00	.50	.23	.69	.91	.27	1.93	1.65	.61	.72	2.19	0.00
	GVW	11.2	2.7	4.8	24.1	17.3	32.6	50.0	25.3	62.3	78.3	34.4	56.5	80.0	0.0
S Lane1	Num	9	1,451	905	7	50	55	3	35	159	42	1	3	15	0
	Flex	.10	.00	.00	1.02	.36	.47	.34	.17	1.15	.77	1.83	1.75	1.96	0.00
	Rigid	.22	.00	.00	1.22	.36	.86	1.17	.19	2.19	1.94	1.88	3.03	3.03	0.00
	GVW	12.2	2.3	4.3	31.4	18.3	33.9	55.9	23.3	63.4	78.7	48.2	71.0	92.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2023

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9