

Idaho Transportation Department

Monthly WIM Distribution for Mar-2024

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	12	2,895	1,682	8	94	65	10	62	261	68	1	2	17	0
	Flex	.04	.00	.00	.53	.19	.35	.34	.16	.98	.57	.77	.78	.90	0.00
	Rigid	.09	.00	.00	.66	.18	.60	.88	.20	1.84	1.51	.77	1.11	1.68	0.00
	GVW	12.1	2.4	4.2	29.9	16.4	31.7	51.2	24.7	62.2	78.6	39.1	57.8	83.4	0.0
N	Num	5	1,454	855	5	50	31	7	32	123	32	0	1	11	0
	Flex	.06	.00	.00	.59	.19	.37	.35	.20	.97	.57	0.00	.84	.80	0.00
	Rigid	.12	.00	.00	.78	.19	.64	.83	.25	1.80	1.47	0.00	1.16	1.57	0.00
	GVW	12.5	2.6	4.5	32.1	16.8	32.4	49.7	26.5	62.3	78.2	0.0	65.8	80.1	0.0
S	Num	7	1,441	826	3	44	34	3	30	139	36	1	2	6	0
	Flex	.04	.00	.00	.44	.19	.35	.26	.12	1.01	.55	.77	1.07	1.03	0.00
	Rigid	.08	.00	.00	.51	.18	.58	.79	.14	1.92	1.47	.77	1.68	1.79	0.00
	GVW	12.2	2.1	3.9	25.6	16.0	31.3	50.5	22.8	62.2	77.8	39.1	61.8	87.2	0.0
N Lane1	Num	5	1,454	855	5	50	31	7	32	123	32	0	1	11	0
	Flex	.06	.00	.00	.59	.19	.37	.35	.20	.97	.57	0.00	.84	.80	0.00
	Rigid	.12	.00	.00	.78	.19	.64	.83	.25	1.80	1.47	0.00	1.16	1.57	0.00
	GVW	12.5	2.6	4.5	32.1	16.8	32.4	49.7	26.5	62.3	78.2	0.0	65.8	80.1	0.0
S Lane1	Num	7	1,441	826	3	44	34	3	30	139	36	1	2	6	0
	Flex	.04	.00	.00	.44	.19	.35	.26	.12	1.01	.55	.77	1.07	1.03	0.00
	Rigid	.08	.00	.00	.51	.18	.58	.79	.14	1.92	1.47	.77	1.68	1.79	0.00
	GVW	12.2	2.1	3.9	25.6	16.0	31.3	50.5	22.8	62.2	77.8	39.1	61.8	87.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2024

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9