

Idaho Transportation Department

Monthly WIM Distribution for May-2024

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	15	3,240	1,963	9	104	67	9	84	251	73	1	3	17	0
	Flex	.03	.00	.00	.51	.19	.35	.22	.13	.90	.54	.76	1.04	1.16	0.00
	Rigid	.07	.00	.00	.59	.19	.60	.73	.15	1.69	1.37	.87	1.62	1.99	0.00
	GVW	11.6	2.5	4.5	28.9	16.4	31.9	50.1	22.3	60.3	75.2	37.0	64.1	84.1	0.0
N	Num	8	1,630	994	5	53	36	5	44	116	40	2	2	10	0
	Flex	.03	.00	.00	.58	.18	.31	.23	.14	.74	.48	2.26	.42	.72	0.00
	Rigid	.06	.00	.00	.70	.18	.53	.73	.17	1.34	1.22	2.44	.64	1.30	0.00
	GVW	11.5	2.8	4.8	31.9	16.9	31.7	49.6	23.3	59.3	74.3	60.4	54.1	76.4	0.0
S	Num	7	1,610	968	5	52	31	5	40	135	34	1	1	7	0
	Flex	.04	.00	.00	.57	.20	.41	.22	.11	1.07	.56	.22	1.40	1.75	0.00
	Rigid	.08	.00	.00	.63	.20	.70	.73	.13	2.05	1.44	.28	2.16	2.86	0.00
	GVW	11.9	2.3	4.2	27.3	15.9	32.3	50.2	21.2	61.4	74.9	29.2	70.9	93.2	0.0
N Lane1	Num	8	1,630	994	5	53	36	5	44	116	40	2	2	10	0
	Flex	.03	.00	.00	.58	.18	.31	.23	.14	.74	.48	2.26	.42	.72	0.00
	Rigid	.06	.00	.00	.70	.18	.53	.73	.17	1.34	1.22	2.44	.64	1.30	0.00
	GVW	11.5	2.8	4.8	31.9	16.9	31.7	49.6	23.3	59.3	74.3	60.4	54.1	76.4	0.0
S Lane1	Num	7	1,610	968	5	52	31	5	40	135	34	1	1	7	0
	Flex	.04	.00	.00	.57	.20	.41	.22	.11	1.07	.56	.22	1.40	1.75	0.00
	Rigid	.08	.00	.00	.63	.20	.70	.73	.13	2.05	1.44	.28	2.16	2.86	0.00
	GVW	11.9	2.3	4.2	27.3	15.9	32.3	50.2	21.2	61.4	74.9	29.2	70.9	93.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2024

Site names: 00169
County: Payette
Funct Class: R Principal Arterial - Other
Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
Daily Factor Grp: 2
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9