

Idaho Transportation Department

Monthly WIM Distribution for Mar-2025

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	48	2,611	1,424	17	94	74	23	55	216	77	2	6	30	0
	Flex	.07	.00	.00	.72	.31	.41	.17	.32	1.36	.82	.86	.84	1.49	0.00
	Rigid	.17	.00	.00	.87	.32	.69	.44	.42	2.62	2.10	1.16	1.36	2.47	0.00
	GVW	8.9	3.1	5.0	18.9	17.0	31.2	35.1	26.7	63.6	78.4	37.4	60.4	83.1	0.0
N	Num	36	1,151	584	14	41	28	21	28	71	45	2	4	19	0
	Flex	.09	.00	.01	.73	.36	.42	.14	.41	1.54	.75	.80	.54	.76	0.00
	Rigid	.21	.01	.01	.90	.37	.76	.35	.53	2.96	1.90	1.10	.98	1.48	0.00
	GVW	8.2	3.6	5.6	16.4	17.2	30.5	32.0	26.3	65.1	76.7	33.7	55.6	75.2	0.0
S	Num	12	1,460	840	4	53	45	4	27	146	32	2	2	11	0
	Flex	.03	.00	.00	.87	.27	.39	.24	.22	1.32	.86	.42	1.31	2.80	0.00
	Rigid	.07	.00	.00	1.06	.28	.64	.72	.28	2.58	2.21	.44	2.00	4.30	0.00
	GVW	10.8	2.7	4.6	28.9	16.6	31.3	47.2	26.9	62.4	80.4	43.9	62.9	97.4	0.0
N Lane1	Num	36	1,151	584	14	41	28	21	28	71	45	2	4	19	0
	Flex	.09	.00	.01	.73	.36	.42	.14	.41	1.54	.75	.80	.54	.76	0.00
	Rigid	.21	.01	.01	.90	.37	.76	.35	.53	2.96	1.90	1.10	.98	1.48	0.00
	GVW	8.2	3.6	5.6	16.4	17.2	30.5	32.0	26.3	65.1	76.7	33.7	55.6	75.2	0.0
S Lane1	Num	12	1,460	840	4	53	45	4	27	146	32	2	2	11	0
	Flex	.03	.00	.00	.87	.27	.39	.24	.22	1.32	.86	.42	1.31	2.80	0.00
	Rigid	.07	.00	.00	1.06	.28	.64	.72	.28	2.58	2.21	.44	2.00	4.30	0.00
	GVW	10.8	2.7	4.6	28.9	16.6	31.3	47.2	26.9	62.4	80.4	43.9	62.9	97.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2025

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9