

Idaho Transportation Department

Monthly WIM Distribution for Feb-2018

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	0	1	1	0	0	0	0	0	1	1	0	0	1	0
	Flex	0.00	.00	.00	0.00	0.00	0.00	0.00	0.00	.13	.12	0.00	0.00	.08	0.00
	Rigid	0.00	.00	.00	0.00	0.00	0.00	0.00	0.00	.13	.12	0.00	0.00	.08	0.00
	GVW	0.0	2.7	4.2	0.0	0.0	0.0	0.0	0.0	26.7	32.7	0.0	0.0	40.4	0.0
SE	Num	0	1	1	0	0	0	0	0	1	1	0	0	1	0
	Flex	0.00	.00	.00	0.00	0.00	0.00	0.00	0.00	.13	.12	0.00	0.00	.08	0.00
	Rigid	0.00	.00	.00	0.00	0.00	0.00	0.00	0.00	.13	.12	0.00	0.00	.08	0.00
	GVW	0.0	2.7	4.2	0.0	0.0	0.0	0.0	0.0	26.7	32.7	0.0	0.0	40.4	0.0
NW	Num	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Flex	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Rigid	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	GVW	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
NW Lane1	Num	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Flex	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Rigid	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	GVW	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
SE Lane1	Num	0	1	1	0	0	0	0	0	1	1	0	0	1	0
	Flex	0.00	.00	.00	0.00	0.00	0.00	0.00	0.00	.13	.12	0.00	0.00	.08	0.00
	Rigid	0.00	.00	.00	0.00	0.00	0.00	0.00	0.00	.13	.12	0.00	0.00	.08	0.00
	GVW	0.0	2.7	4.2	0.0	0.0	0.0	0.0	0.0	26.7	32.7	0.0	0.0	40.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2018

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9