

Idaho Transportation Department

Monthly WIM Distribution for Oct-2018

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	736	1,078	1	33	157	6	25	220	161	3	4	288	0
	Flex	.00	.00	.00	.07	1.04	.37	1.01	.38	1.04	1.11	2.94	1.19	.99	0.00
	Rigid	.00	.00	.00	.11	1.13	.66	1.74	.53	2.00	2.65	3.57	1.66	1.83	0.00
	GVW	1.7	3.3	4.0	12.7	22.3	24.5	42.3	25.8	49.5	74.4	45.4	65.8	69.9	0.0
SE	Num	2	378	547	1	19	73	3	10	115	80	3	3	156	0
	Flex	.00	.00	.00	.10	.71	.36	.44	.44	.56	.97	3.28	.97	.25	0.00
	Rigid	.00	.00	.00	.14	.73	.68	.66	.67	.97	2.18	4.14	1.35	.38	0.00
	GVW	1.1	3.3	4.2	16.4	21.4	24.2	36.6	26.6	41.9	68.2	56.4	62.5	41.7	0.0
NW	Num	1	783	531	1	14	83	2	15	105	81	3	1	132	0
	Flex	.00	.00	.00	.11	1.46	.38	1.50	.35	1.58	1.27	3.16	1.55	1.85	0.00
	Rigid	.00	.00	.00	.19	1.64	.65	2.52	.45	3.18	3.15	3.52	2.18	3.54	0.00
	GVW	2.6	3.5	3.9	18.6	23.4	24.8	45.8	25.5	58.2	80.1	35.8	70.1	103.2	0.0
NW Lane1	Num	1	783	531	1	14	83	2	15	105	81	3	1	132	0
	Flex	.00	.00	.00	.11	1.46	.38	1.50	.35	1.58	1.27	3.16	1.55	1.85	0.00
	Rigid	.00	.00	.00	.19	1.64	.65	2.52	.45	3.18	3.15	3.52	2.18	3.54	0.00
	GVW	2.6	3.5	3.9	18.6	23.4	24.8	45.8	25.5	58.2	80.1	35.8	70.1	103.2	0.0
SE Lane1	Num	2	378	547	1	19	73	3	10	115	80	3	3	156	0
	Flex	.00	.00	.00	.10	.71	.36	.44	.44	.56	.97	3.28	.97	.25	0.00
	Rigid	.00	.00	.00	.14	.73	.68	.66	.67	.97	2.18	4.14	1.35	.38	0.00
	GVW	1.1	3.3	4.2	16.4	21.4	24.2	36.6	26.6	41.9	68.2	56.4	62.5	41.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2018

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9