

Idaho Transportation Department

Monthly WIM Distribution for Dec-2018

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	1,339	819	2	20	19	2	12	168	125	2	4	373	0
	Flex	.00	.00	.00	.34	.48	.44	.53	.26	.70	.84	.42	1.02	.93	0.00
	Rigid	.00	.00	.00	.45	.50	.67	.64	.31	1.26	1.98	.50	1.40	1.71	0.00
	GVW	1.8	3.5	4.2	20.8	18.2	27.0	29.4	22.5	46.2	71.2	37.1	59.2	77.2	0.0
SE	Num	1	686	421	2	12	10	2	6	89	61	1	2	189	0
	Flex	.00	.00	.00	.30	.44	.42	.55	.29	.40	.66	.13	.47	.18	0.00
	Rigid	.00	.00	.00	.37	.45	.67	.67	.36	.63	1.41	.21	.50	.25	0.00
	GVW	2.7	3.5	4.3	19.7	18.3	28.3	33.3	21.2	38.9	58.9	28.6	46.1	40.1	0.0
NW	Num	1	653	398	1	9	9	1	7	79	64	1	2	184	0
	Flex	.00	.00	.00	.42	.51	.48	.98	.24	1.10	.94	.96	1.88	1.70	0.00
	Rigid	.00	.00	.00	.61	.54	.71	1.15	.28	2.11	2.30	.98	2.79	3.25	0.00
	GVW	1.6	3.5	4.1	26.6	18.1	25.9	29.0	24.8	55.6	79.7	38.8	77.8	115.4	0.0
NW Lane1	Num	1	653	398	1	9	9	1	7	79	64	1	2	184	0
	Flex	.00	.00	.00	.42	.51	.48	.98	.24	1.10	.94	.96	1.88	1.70	0.00
	Rigid	.00	.00	.00	.61	.54	.71	1.15	.28	2.11	2.30	.98	2.79	3.25	0.00
	GVW	1.6	3.5	4.1	26.6	18.1	25.9	29.0	24.8	55.6	79.7	38.8	77.8	115.4	0.0
SE Lane1	Num	1	686	421	2	12	10	2	6	89	61	1	2	189	0
	Flex	.00	.00	.00	.30	.44	.42	.55	.29	.40	.66	.13	.47	.18	0.00
	Rigid	.00	.00	.00	.37	.45	.67	.67	.36	.63	1.41	.21	.50	.25	0.00
	GVW	2.7	3.5	4.3	19.7	18.3	28.3	33.3	21.2	38.9	58.9	28.6	46.1	40.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2018

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9