

Idaho Transportation Department

Monthly WIM Distribution for Jan-2020

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,344	826	1	23	28	2	14	195	112	2	2	319	0
	Flex	.00	.00	.00	.45	.73	.45	.40	.30	.83	.94	.39	.97	1.09	0.00
	Rigid	.00	.00	.00	.58	.77	.67	.58	.39	1.54	2.26	.56	1.14	2.00	0.00
	GVW	2.0	3.6	4.1	27.1	21.1	26.3	32.5	23.7	48.9	73.4	28.9	55.6	78.9	0.0
SE	Num	1	696	426	1	12	16	2	6	104	55	1	1	164	0
	Flex	.00	.00	.00	.36	.83	.43	.56	.33	.51	.74	1.06	.65	.20	0.00
	Rigid	.00	.00	.00	.45	.87	.64	.64	.48	.88	1.67	1.10	.70	.26	0.00
	GVW	2.2	3.7	4.2	28.5	21.7	26.8	31.1	23.5	42.3	66.0	33.1	51.1	40.2	0.0
NW	Num	2	648	400	1	11	12	2	8	91	57	2	1	155	0
	Flex	.00	.00	.00	.47	.73	.46	.63	.26	1.22	1.06	.28	1.13	2.05	0.00
	Rigid	.00	.00	.00	.59	.78	.66	1.05	.31	2.36	2.62	.55	1.31	3.87	0.00
	GVW	1.9	3.6	3.9	25.9	20.7	25.3	37.0	24.0	56.8	78.4	32.2	60.4	120.2	0.0
NW Lane1	Num	2	648	400	1	11	12	2	8	91	57	2	1	155	0
	Flex	.00	.00	.00	.47	.73	.46	.63	.26	1.22	1.06	.28	1.13	2.05	0.00
	Rigid	.00	.00	.00	.59	.78	.66	1.05	.31	2.36	2.62	.55	1.31	3.87	0.00
	GVW	1.9	3.6	3.9	25.9	20.7	25.3	37.0	24.0	56.8	78.4	32.2	60.4	120.2	0.0
SE Lane1	Num	1	696	426	1	12	16	2	6	104	55	1	1	164	0
	Flex	.00	.00	.00	.36	.83	.43	.56	.33	.51	.74	1.06	.65	.20	0.00
	Rigid	.00	.00	.00	.45	.87	.64	.64	.48	.88	1.67	1.10	.70	.26	0.00
	GVW	2.2	3.7	4.2	28.5	21.7	26.8	31.1	23.5	42.3	66.0	33.1	51.1	40.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2020

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9