

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	1,456	859	1	22	29	3	14	217	120	2	1	334	0
	Flex	.00	.00	.00	1.00	.57	.44	.75	.21	.81	.90	.37	.48	1.00	0.00
	Rigid	.00	.00	.00	1.41	.59	.66	1.05	.24	1.48	2.17	.47	.50	1.76	0.00
	GVW	2.6	3.6	4.1	37.2	19.1	26.1	35.7	22.0	49.2	74.5	28.8	44.6	77.8	0.0
SE	Num	1	747	440	1	11	15	2	8	113	57	1	1	170	0
	Flex	.00	.00	.00	1.18	.59	.50	.92	.20	.70	.91	.45	.26	.21	0.00
	Rigid	.00	.00	.00	1.79	.60	.79	1.21	.24	1.25	2.03	.52	.27	.26	0.00
	GVW	3.6	3.6	4.1	42.3	19.4	27.6	37.2	19.3	45.5	66.0	29.9	31.3	40.2	0.0
NW	Num	1	709	419	1	11	14	1	7	104	64	1	2	164	0
	Flex	.00	.00	.00	.34	.54	.33	.98	.22	.93	.89	.11	.71	1.82	0.00
	Rigid	.00	.00	.00	.43	.57	.48	1.30	.25	1.76	2.26	.29	.73	3.32	0.00
	GVW	2.4	3.5	4.0	30.0	19.4	24.1	38.1	23.8	53.4	79.7	17.1	57.9	116.9	0.0
NW Lane1	Num	1	709	419	1	11	14	1	7	104	64	1	2	164	0
	Flex	.00	.00	.00	.34	.54	.33	.98	.22	.93	.89	.11	.71	1.82	0.00
	Rigid	.00	.00	.00	.43	.57	.48	1.30	.25	1.76	2.26	.29	.73	3.32	0.00
	GVW	2.4	3.5	4.0	30.0	19.4	24.1	38.1	23.8	53.4	79.7	17.1	57.9	116.9	0.0
SE Lane1	Num	1	747	440	1	11	15	2	8	113	57	1	1	170	0
	Flex	.00	.00	.00	1.18	.59	.50	.92	.20	.70	.91	.45	.26	.21	0.00
	Rigid	.00	.00	.00	1.79	.60	.79	1.21	.24	1.25	2.03	.52	.27	.26	0.00
	GVW	3.6	3.6	4.1	42.3	19.4	27.6	37.2	19.3	45.5	66.0	29.9	31.3	40.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9