

Idaho Transportation Department

Monthly WIM Distribution for Apr-2020

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,311	1,059	2	34	72	3	41	210	118	1	3	59	0
	Flex	.00	.00	.00	.96	1.09	.78	.56	.23	.90	1.06	.08	.41	1.82	0.00
	Rigid	.00	.00	.00	1.01	1.21	1.44	.79	.29	1.68	2.61	.07	.46	2.68	0.00
	GVW	1.4	3.6	4.1	17.3	21.0	31.3	34.0	19.7	49.9	73.3	20.7	46.9	66.7	0.0
SE	Num	1	681	542	2	18	37	2	21	110	60	1	2	32	0
	Flex	.00	.00	.00	.41	1.24	.78	.59	.25	.60	.93	.12	.41	1.18	0.00
	Rigid	.00	.00	.00	.42	1.37	1.45	.85	.31	1.07	2.23	.12	.46	1.86	0.00
	GVW	1.8	3.7	4.1	18.5	22.1	31.8	35.6	19.7	44.1	69.3	23.7	43.2	61.9	0.0
NW	Num	1	631	518	1	16	35	2	20	100	58	1	2	27	0
	Flex	.00	.00	.00	.87	.89	.81	.18	.21	1.25	1.15	.03	.43	2.60	0.00
	Rigid	.00	.00	.00	.92	.99	1.48	.37	.27	2.41	2.81	.03	.47	3.65	0.00
	GVW	1.3	3.5	4.1	14.8	19.3	30.8	26.0	19.6	56.7	75.0	18.3	48.7	73.7	0.0
NW Lane1	Num	1	631	518	1	16	35	2	20	100	58	1	2	27	0
	Flex	.00	.00	.00	.87	.89	.81	.18	.21	1.25	1.15	.03	.43	2.60	0.00
	Rigid	.00	.00	.00	.92	.99	1.48	.37	.27	2.41	2.81	.03	.47	3.65	0.00
	GVW	1.3	3.5	4.1	14.8	19.3	30.8	26.0	19.6	56.7	75.0	18.3	48.7	73.7	0.0
SE Lane1	Num	1	681	542	2	18	37	2	21	110	60	1	2	32	0
	Flex	.00	.00	.00	.41	1.24	.78	.59	.25	.60	.93	.12	.41	1.18	0.00
	Rigid	.00	.00	.00	.42	1.37	1.45	.85	.31	1.07	2.23	.12	.46	1.86	0.00
	GVW	1.8	3.7	4.1	18.5	22.1	31.8	35.6	19.7	44.1	69.3	23.7	43.2	61.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2020

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9