

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2020

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1,519	1,797	1,210	1	32	83	3	52	189	90	2	1	41	0
	Flex	.06	.00	.00	.52	.75	.66	.23	.21	1.13	.91	.04	.59	1.59	0.00
	Rigid	.10	.00	.00	.64	.81	1.07	.65	.25	2.12	2.18	.04	.57	2.43	0.00
	GVW	5.6	3.9	4.0	22.5	20.5	29.5	32.4	16.8	52.3	72.3	20.4	50.3	63.8	0.0
SE	Num	1,322	914	616	1	17	42	3	27	99	41	1	1	23	0
	Flex	.08	.00	.00	1.17	.82	.82	.24	.26	.82	.96	.02	.32	.53	0.00
	Rigid	.14	.00	.00	1.52	.88	1.36	.89	.30	1.42	2.08	.02	.33	.84	0.00
	GVW	7.8	4.0	4.1	41.5	20.8	30.5	36.5	16.8	44.5	65.6	18.4	52.4	48.8	0.0
NW	Num	796	883	594	1	15	41	2	25	90	49	1	1	18	0
	Flex	.07	.00	.00	.43	.70	.49	.19	.17	1.48	.91	.10	.86	3.09	0.00
	Rigid	.13	.00	.00	.46	.76	.75	.31	.21	2.92	2.28	.09	.82	4.66	0.00
	GVW	6.0	3.8	4.0	16.4	20.4	28.4	28.8	16.7	61.1	76.2	25.4	48.3	82.5	0.0
NW Lane1	Num	796	883	594	1	15	41	2	25	90	49	1	1	18	0
	Flex	.07	.00	.00	.43	.70	.49	.19	.17	1.48	.91	.10	.86	3.09	0.00
	Rigid	.13	.00	.00	.46	.76	.75	.31	.21	2.92	2.28	.09	.82	4.66	0.00
	GVW	6.0	3.8	4.0	16.4	20.4	28.4	28.8	16.7	61.1	76.2	25.4	48.3	82.5	0.0
SE Lane1	Num	1,322	914	616	1	17	42	3	27	99	41	1	1	23	0
	Flex	.08	.00	.00	1.17	.82	.82	.24	.26	.82	.96	.02	.32	.53	0.00
	Rigid	.14	.00	.00	1.52	.88	1.36	.89	.30	1.42	2.08	.02	.33	.84	0.00
	GVW	7.8	4.0	4.1	41.5	20.8	30.5	36.5	16.8	44.5	65.6	18.4	52.4	48.8	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2020

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9