

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2021

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,861	1,210	1	32	123	5	19	215	184	4	1	306	0
	Flex	.00	.00	.00	.44	.85	.45	.36	.35	.79	1.02	.07	.54	1.10	0.00
	Rigid	.00	.00	.00	.57	.92	.78	.69	.46	1.48	2.43	.13	.61	2.06	0.00
	GVW	2.2	3.8	3.9	28.1	21.2	27.0	35.3	22.6	47.4	73.2	21.4	43.3	80.0	0.0
SE	Num	1	953	616	1	17	62	4	9	121	83	2	1	157	0
	Flex	.00	.00	.00	.48	.82	.41	.45	.37	.52	.61	.06	1.10	.16	0.00
	Rigid	.00	.00	.00	.65	.88	.73	.93	.48	.93	1.32	.12	1.37	.21	0.00
	GVW	3.0	3.9	3.9	28.4	21.4	26.7	41.3	23.1	41.7	57.5	20.8	60.9	38.6	0.0
NW	Num	2	908	594	1	15	60	2	10	94	101	3	1	149	0
	Flex	.00	.00	.00	.82	.87	.49	.25	.32	1.23	1.29	.10	.23	2.09	0.00
	Rigid	.00	.00	.00	1.12	.94	.83	.32	.50	2.41	3.18	.21	.24	4.01	0.00
	GVW	1.9	3.6	4.0	31.9	20.9	27.4	26.9	22.4	55.9	84.4	23.6	35.5	123.5	0.0
NW Lane1	Num	2	908	594	1	15	60	2	10	94	101	3	1	149	0
	Flex	.00	.00	.00	.82	.87	.49	.25	.32	1.23	1.29	.10	.23	2.09	0.00
	Rigid	.00	.00	.00	1.12	.94	.83	.32	.50	2.41	3.18	.21	.24	4.01	0.00
	GVW	1.9	3.6	4.0	31.9	20.9	27.4	26.9	22.4	55.9	84.4	23.6	35.5	123.5	0.0
SE Lane1	Num	1	953	616	1	17	62	4	9	121	83	2	1	157	0
	Flex	.00	.00	.00	.48	.82	.41	.45	.37	.52	.61	.06	1.10	.16	0.00
	Rigid	.00	.00	.00	.65	.88	.73	.93	.48	.93	1.32	.12	1.37	.21	0.00
	GVW	3.0	3.9	3.9	28.4	21.4	26.7	41.3	23.1	41.7	57.5	20.8	60.9	38.6	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2021

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp: 5

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9