

Idaho Transportation Department

Monthly WIM Distribution for Nov-2021

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,747	1,085	2	31	57	4	18	200	174	2	1	311	0
	Flex	.00	.00	.00	.36	.88	.39	.57	.15	.57	.93	.31	.81	.89	0.00
	Rigid	.00	.00	.00	.40	1.11	.63	.94	.20	.99	2.18	.31	.92	1.64	0.00
	GVW	2.4	3.8	3.9	25.6	28.1	25.9	37.3	19.8	44.8	74.9	21.7	44.9	76.4	0.0
SE	Num	1	892	557	1	18	30	3	9	113	81	2	1	161	0
	Flex	.00	.00	.00	.33	.76	.41	.69	.19	.38	.64	.95	3.78	.24	0.00
	Rigid	.00	.00	.00	.37	.92	.69	1.01	.25	.63	1.48	.95	4.45	.34	0.00
	GVW	2.4	4.0	3.8	28.1	27.4	27.1	42.2	20.3	40.2	60.2	33.6	78.2	41.9	0.0
NW	Num	1	856	528	1	13	28	3	9	92	93	2	1	151	0
	Flex	.00	.00	.00	.45	1.11	.39	.48	.13	.87	1.09	.32	.22	1.58	0.00
	Rigid	.00	.00	.00	.51	1.49	.58	.94	.16	1.61	2.57	.32	.22	3.02	0.00
	GVW	2.2	3.7	4.0	22.0	29.7	24.7	35.9	19.5	52.5	83.4	23.8	37.7	112.9	0.0
NW Lane1	Num	1	856	528	1	13	28	3	9	92	93	2	1	151	0
	Flex	.00	.00	.00	.45	1.11	.39	.48	.13	.87	1.09	.32	.22	1.58	0.00
	Rigid	.00	.00	.00	.51	1.49	.58	.94	.16	1.61	2.57	.32	.22	3.02	0.00
	GVW	2.2	3.7	4.0	22.0	29.7	24.7	35.9	19.5	52.5	83.4	23.8	37.7	112.9	0.0
SE Lane1	Num	1	892	557	1	18	30	3	9	113	81	2	1	161	0
	Flex	.00	.00	.00	.33	.76	.41	.69	.19	.38	.64	.95	3.78	.24	0.00
	Rigid	.00	.00	.00	.37	.92	.69	1.01	.25	.63	1.48	.95	4.45	.34	0.00
	GVW	2.4	4.0	3.8	28.1	27.4	27.1	42.2	20.3	40.2	60.2	33.6	78.2	41.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2021

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9