

Idaho Transportation Department

Monthly WIM Distribution for Dec-2021

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	1,450	879	1	29	26	3	13	178	142	4	1	263	0
	Flex	.00	.00	.00	.60	.90	.59	.95	.40	.73	.95	3.73	1.00	1.31	0.00
	Rigid	.00	.00	.00	.71	1.22	.89	1.41	.52	1.37	2.22	4.14	1.33	2.53	0.00
	GVW	1.5	3.9	3.9	28.0	30.2	27.8	44.3	25.2	46.0	72.5	58.3	50.9	83.2	0.0
SE	Num	0	741	455	1	17	13	2	6	100	59	2	1	135	0
	Flex	0.00	.00	.00	.67	.83	.41	1.08	.55	.44	.47	1.96	1.43	.18	0.00
	Rigid	0.00	.00	.00	.79	1.13	.57	1.36	.69	.75	1.00	2.27	1.72	.26	0.00
	GVW	0.0	4.0	3.9	29.0	31.2	26.8	43.6	26.8	41.0	51.8	45.5	53.5	41.7	0.0
NW	Num	1	708	423	1	12	13	2	7	78	82	3	1	128	0
	Flex	.00	.00	.00	.25	.97	.76	.36	.28	1.16	1.23	4.77	.37	2.52	0.00
	Rigid	.00	.00	.00	.33	1.27	1.20	.75	.39	2.27	2.96	5.24	.62	4.98	0.00
	GVW	1.5	3.7	3.8	21.3	27.0	28.6	33.9	24.3	53.5	83.8	65.2	45.2	128.2	0.0
NW Lane1	Num	1	708	423	1	12	13	2	7	78	82	3	1	128	0
	Flex	.00	.00	.00	.25	.97	.76	.36	.28	1.16	1.23	4.77	.37	2.52	0.00
	Rigid	.00	.00	.00	.33	1.27	1.20	.75	.39	2.27	2.96	5.24	.62	4.98	0.00
	GVW	1.5	3.7	3.8	21.3	27.0	28.6	33.9	24.3	53.5	83.8	65.2	45.2	128.2	0.0
SE Lane1	Num	0	741	455	1	17	13	2	6	100	59	2	1	135	0
	Flex	0.00	.00	.00	.67	.83	.41	1.08	.55	.44	.47	1.96	1.43	.18	0.00
	Rigid	0.00	.00	.00	.79	1.13	.57	1.36	.69	.75	1.00	2.27	1.72	.26	0.00
	GVW	0.0	4.0	3.9	29.0	31.2	26.8	43.6	26.8	41.0	51.8	45.5	53.5	41.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2021

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9