

Idaho Transportation Department

Monthly WIM Distribution for Apr-2022

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,738	1,111	1	30	92	8	26	267	169	1	2	44	0
	Flex	.00	.00	.00	.63	.74	.57	.55	.29	.93	.87	.06	1.65	1.82	0.00
	Rigid	.00	.00	.00	.74	.83	.99	.87	.38	1.73	2.06	.09	1.89	2.78	0.00
	GVW	2.4	3.8	3.9	23.5	20.7	28.3	40.9	22.8	50.1	70.5	21.0	62.8	71.6	0.0
SE	Num	2	890	563	1	15	47	5	12	138	84	1	1	26	0
	Flex	.00	.00	.00	.63	.94	.63	.46	.31	.65	.76	.09	3.28	1.44	0.00
	Rigid	.00	.00	.00	.73	1.05	1.11	.78	.41	1.17	1.69	.13	3.86	2.49	0.00
	GVW	2.6	3.9	3.9	24.4	23.0	29.9	42.3	22.1	45.5	63.7	26.3	74.5	72.1	0.0
NW	Num	2	849	548	1	14	45	3	14	130	85	1	1	18	0
	Flex	.00	.00	.00	.15	.59	.52	.50	.29	1.23	.98	.04	1.07	2.39	0.00
	Rigid	.00	.00	.00	.19	.65	.87	.71	.37	2.36	2.39	.05	1.18	3.26	0.00
	GVW	2.3	3.7	4.0	16.3	18.8	26.8	33.8	23.4	55.3	75.6	17.1	57.9	69.5	0.0
NW Lane1	Num	2	849	548	1	14	45	3	14	130	85	1	1	18	0
	Flex	.00	.00	.00	.15	.59	.52	.50	.29	1.23	.98	.04	1.07	2.39	0.00
	Rigid	.00	.00	.00	.19	.65	.87	.71	.37	2.36	2.39	.05	1.18	3.26	0.00
	GVW	2.3	3.7	4.0	16.3	18.8	26.8	33.8	23.4	55.3	75.6	17.1	57.9	69.5	0.0
SE Lane1	Num	2	890	563	1	15	47	5	12	138	84	1	1	26	0
	Flex	.00	.00	.00	.63	.94	.63	.46	.31	.65	.76	.09	3.28	1.44	0.00
	Rigid	.00	.00	.00	.73	1.05	1.11	.78	.41	1.17	1.69	.13	3.86	2.49	0.00
	GVW	2.6	3.9	3.9	24.4	23.0	29.9	42.3	22.1	45.5	63.7	26.3	74.5	72.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2022

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9