

Idaho Transportation Department

Monthly WIM Distribution for Jul-2022

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,811	1,254	1	29	74	5	54	200	109	2	3	41	0
	Flex	.00	.00	.00	.21	.46	.42	.45	.18	.79	.78	.11	1.14	1.17	0.00
	Rigid	.00	.00	.00	.28	.48	.66	.75	.23	1.44	1.73	.29	1.29	1.72	0.00
	GVW	1.9	3.8	4.2	23.0	18.0	26.2	38.0	18.1	48.4	70.0	22.4	51.2	66.0	0.0
SE	Num	2	939	658	1	16	38	3	24	103	61	2	2	25	0
	Flex	.00	.00	.00	.25	.48	.52	.47	.17	.46	.73	.17	2.36	.90	0.00
	Rigid	.00	.00	.00	.32	.50	.88	.89	.22	.75	1.63	.42	2.68	1.55	0.00
	GVW	2.1	4.0	4.3	25.2	18.5	28.5	41.4	16.7	42.0	67.7	26.9	71.1	69.1	0.0
NW	Num	2	873	597	1	13	36	2	30	98	48	1	2	17	0
	Flex	.00	.00	.00	.11	.41	.32	.48	.18	1.17	.77	.01	.79	1.63	0.00
	Rigid	.00	.00	.00	.12	.43	.44	.61	.23	2.24	1.68	.03	.88	2.11	0.00
	GVW	2.1	3.7	4.0	15.6	17.6	24.0	33.4	18.8	56.2	68.8	16.5	46.0	61.3	0.0
NW Lane1	Num	2	873	597	1	13	36	2	30	98	48	1	2	17	0
	Flex	.00	.00	.00	.11	.41	.32	.48	.18	1.17	.77	.01	.79	1.63	0.00
	Rigid	.00	.00	.00	.12	.43	.44	.61	.23	2.24	1.68	.03	.88	2.11	0.00
	GVW	2.1	3.7	4.0	15.6	17.6	24.0	33.4	18.8	56.2	68.8	16.5	46.0	61.3	0.0
SE Lane1	Num	2	939	658	1	16	38	3	24	103	61	2	2	25	0
	Flex	.00	.00	.00	.25	.48	.52	.47	.17	.46	.73	.17	2.36	.90	0.00
	Rigid	.00	.00	.00	.32	.50	.88	.89	.22	.75	1.63	.42	2.68	1.55	0.00
	GVW	2.1	4.0	4.3	25.2	18.5	28.5	41.4	16.7	42.0	67.7	26.9	71.1	69.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2022

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9