

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2022

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,335	861	2	23	31	3	14	169	92	2	2	299	0
	Flex	.00	.00	.00	1.67	.79	.53	.29	.39	.84	.97	.41	1.27	1.30	0.00
	Rigid	.00	.00	.00	2.31	1.06	.76	.35	.50	1.56	2.25	.91	1.42	2.53	0.00
	GVW	2.4	4.0	3.9	36.0	25.4	28.5	27.5	26.8	48.6	71.7	40.2	52.5	83.3	0.0
SE	Num	1	679	441	1	12	16	2	6	92	42	2	1	157	0
	Flex	.00	.00	.00	.68	.48	.51	.25	.37	.39	.62	.24	1.71	.15	0.00
	Rigid	.00	.00	.00	1.14	.56	.74	.31	.49	.64	1.26	.59	2.02	.20	0.00
	GVW	1.7	3.9	4.0	35.4	22.6	29.3	27.3	26.4	40.3	56.4	39.7	56.5	42.2	0.0
NW	Num	2	656	420	1	12	16	2	8	77	51	1	2	142	0
	Flex	.00	.00	.00	2.25	1.14	.56	.36	.41	1.39	1.22	.41	1.17	2.59	0.00
	Rigid	.00	.00	.00	3.24	1.58	.80	.38	.52	2.68	2.93	.86	1.27	5.13	0.00
	GVW	2.3	4.0	3.8	39.5	29.0	28.0	25.9	27.1	59.1	80.1	35.6	51.0	129.0	0.0
NW Lane1	Num	2	656	420	1	12	16	2	8	77	51	1	2	142	0
	Flex	.00	.00	.00	2.25	1.14	.56	.36	.41	1.39	1.22	.41	1.17	2.59	0.00
	Rigid	.00	.00	.00	3.24	1.58	.80	.38	.52	2.68	2.93	.86	1.27	5.13	0.00
	GVW	2.3	4.0	3.8	39.5	29.0	28.0	25.9	27.1	59.1	80.1	35.6	51.0	129.0	0.0
SE Lane1	Num	1	679	441	1	12	16	2	6	92	42	2	1	157	0
	Flex	.00	.00	.00	.68	.48	.51	.25	.37	.39	.62	.24	1.71	.15	0.00
	Rigid	.00	.00	.00	1.14	.56	.74	.31	.49	.64	1.26	.59	2.02	.20	0.00
	GVW	1.7	3.9	4.0	35.4	22.6	29.3	27.3	26.4	40.3	56.4	39.7	56.5	42.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2022

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9