

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2023

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,769	1,406	3	39	108	8	36	267	182	2	2	64	0
	Flex	.00	.00	.00	.74	1.00	.79	.61	.27	.90	1.04	.12	.73	1.73	0.00
	Rigid	.00	.00	.00	.90	1.11	1.40	.97	.36	1.62	2.46	.36	.80	2.61	0.00
	GVW	2.1	3.9	3.9	27.7	22.0	31.4	39.1	23.9	48.2	74.7	26.8	47.2	75.8	0.0
SE	Num	2	904	724	2	22	53	6	17	146	84	2	1	35	0
	Flex	.00	.00	.00	.69	1.01	.98	.71	.24	.61	.86	.14	.64	1.11	0.00
	Rigid	.00	.00	.00	.77	1.09	1.85	1.05	.29	1.01	1.90	.41	.69	1.88	0.00
	GVW	2.0	4.0	3.9	28.0	21.8	34.8	40.7	23.3	44.4	71.0	28.6	49.4	75.2	0.0
NW	Num	2	865	682	1	17	55	3	19	121	98	2	1	29	0
	Flex	.00	.00	.00	.99	1.00	.61	.64	.30	1.30	1.20	.06	1.46	2.41	0.00
	Rigid	.00	.00	.00	1.34	1.13	.98	.97	.41	2.46	2.89	.08	1.62	3.26	0.00
	GVW	2.0	3.7	3.9	29.8	22.1	28.3	38.7	24.4	53.2	76.8	22.4	53.9	74.1	0.0
NW Lane1	Num	2	865	682	1	17	55	3	19	121	98	2	1	29	0
	Flex	.00	.00	.00	.99	1.00	.61	.64	.30	1.30	1.20	.06	1.46	2.41	0.00
	Rigid	.00	.00	.00	1.34	1.13	.98	.97	.41	2.46	2.89	.08	1.62	3.26	0.00
	GVW	2.0	3.7	3.9	29.8	22.1	28.3	38.7	24.4	53.2	76.8	22.4	53.9	74.1	0.0
SE Lane1	Num	2	904	724	2	22	53	6	17	146	84	2	1	35	0
	Flex	.00	.00	.00	.69	1.01	.98	.71	.24	.61	.86	.14	.64	1.11	0.00
	Rigid	.00	.00	.00	.77	1.09	1.85	1.05	.29	1.01	1.90	.41	.69	1.88	0.00
	GVW	2.0	4.0	3.9	28.0	21.8	34.8	40.7	23.3	44.4	71.0	28.6	49.4	75.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2023

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 5

UNCLS
-------

Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9