

Idaho Transportation Department

Monthly WIM Distribution for Jul-2023

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	2,263	1,770	2	45	89	7	53	179	97	2	2	57	0
	Flex	.00	.00	.00	1.01	.65	.48	.56	.25	.77	.71	.34	.95	1.00	0.00
	Rigid	.00	.00	.00	1.39	.69	.75	.89	.33	1.36	1.49	.54	1.11	1.54	0.00
	GVW	2.7	3.9	4.1	31.6	19.4	27.6	37.3	20.7	49.7	61.3	27.2	48.3	62.1	0.0
SE	Num	2	1,268	960	1	25	44	5	28	115	63	2	1	40	0
	Flex	.00	.00	.00	.58	.53	.46	.57	.26	.62	.73	.46	1.04	.78	0.00
	Rigid	.00	.00	.00	.71	.55	.73	.88	.33	1.06	1.58	.73	1.23	1.25	0.00
	GVW	2.2	3.8	4.2	23.9	19.0	28.8	39.7	20.0	47.2	65.2	30.4	51.8	61.9	0.0
NW	Num	2	995	810	1	20	44	2	25	64	33	1	2	17	0
	Flex	.00	.00	.00	1.35	.82	.50	.45	.25	1.15	.67	.02	.55	1.52	0.00
	Rigid	.00	.00	.00	1.80	.89	.77	.98	.34	2.15	1.36	.03	.57	2.25	0.00
	GVW	2.9	3.9	3.9	35.6	19.9	26.8	35.2	21.6	56.0	53.9	17.2	39.3	59.4	0.0
NW Lane1	Num	2	995	810	1	20	44	2	25	64	33	1	2	17	0
	Flex	.00	.00	.00	1.35	.82	.50	.45	.25	1.15	.67	.02	.55	1.52	0.00
	Rigid	.00	.00	.00	1.80	.89	.77	.98	.34	2.15	1.36	.03	.57	2.25	0.00
	GVW	2.9	3.9	3.9	35.6	19.9	26.8	35.2	21.6	56.0	53.9	17.2	39.3	59.4	0.0
SE Lane1	Num	2	1,268	960	1	25	44	5	28	115	63	2	1	40	0
	Flex	.00	.00	.00	.58	.53	.46	.57	.26	.62	.73	.46	1.04	.78	0.00
	Rigid	.00	.00	.00	.71	.55	.73	.88	.33	1.06	1.58	.73	1.23	1.25	0.00
	GVW	2.2	3.8	4.2	23.9	19.0	28.8	39.7	20.0	47.2	65.2	30.4	51.8	61.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2023

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 5

UNCLS

Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9