

Idaho Transportation Department

Monthly WIM Distribution for May-2024

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,890	1,390	2	40	80	8	36	193	186	2	1	52	0
	Flex	.00	.00	.00	1.39	.63	.67	1.11	.28	.87	1.02	.41	.39	1.83	0.00
	Rigid	.00	.00	.00	1.77	.68	1.14	1.50	.37	1.56	2.29	.47	.47	2.59	0.00
	GVW	1.5	3.8	3.9	34.6	18.7	29.6	40.8	20.6	47.8	66.6	27.0	36.7	68.4	0.0
SE	Num	1	972	713	1	21	38	7	17	105	87	2	1	30	0
	Flex	.00	.00	.00	.90	.60	.58	.60	.29	.60	.74	.37	.55	1.10	0.00
	Rigid	.00	.00	.00	1.20	.64	.99	.96	.40	1.01	1.53	.46	.66	1.65	0.00
	GVW	1.7	3.9	3.9	31.6	18.8	30.5	41.1	21.0	43.0	58.8	23.5	46.7	66.7	0.0
NW	Num	1	918	677	1	19	42	2	18	88	99	2	1	22	0
	Flex	.00	.00	.00	1.59	.66	.81	1.30	.27	1.18	1.24	.42	.01	2.94	0.00
	Rigid	.00	.00	.00	1.88	.71	1.40	1.52	.36	2.21	2.86	.47	.01	4.04	0.00
	GVW	1.6	3.6	3.8	34.6	18.8	29.8	33.4	20.3	53.3	72.4	27.4	16.1	74.3	0.0
NW Lane1	Num	1	918	677	1	19	42	2	18	88	99	2	1	22	0
	Flex	.00	.00	.00	1.59	.66	.81	1.30	.27	1.18	1.24	.42	.01	2.94	0.00
	Rigid	.00	.00	.00	1.88	.71	1.40	1.52	.36	2.21	2.86	.47	.01	4.04	0.00
	GVW	1.6	3.6	3.8	34.6	18.8	29.8	33.4	20.3	53.3	72.4	27.4	16.1	74.3	0.0
SE Lane1	Num	1	972	713	1	21	38	7	17	105	87	2	1	30	0
	Flex	.00	.00	.00	.90	.60	.58	.60	.29	.60	.74	.37	.55	1.10	0.00
	Rigid	.00	.00	.00	1.20	.64	.99	.96	.40	1.01	1.53	.46	.66	1.65	0.00
	GVW	1.7	3.9	3.9	31.6	18.8	30.5	41.1	21.0	43.0	58.8	23.5	46.7	66.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2024

Site names: 00179
County: Power
Funct Class: R Minor Arterial - Other
Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
Daily Factor Grp: 2
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 5

		UNCLS
--	--	-------

Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9