Idaho Transportation Department

Monthly WIM Distribution for Jun-2024

Site names: 00179
County: Power
Funct Class: R Minor Arterial - Other
Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
Daily Factor Grp: 2
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,966	1,426	1	42	84	5	52	216	256	2	1	46	0
	Flex	.00	.00	.00	.38	.48	.56	.61	.20	.68	.80	.32	.19	1.55	0.00
	Rigid	.00	.00	.00	.51	.50	.88	.84	.30	1.20	1.87	.71	.21	2.24	0.00
	GVW	2.2	3.9	3.9	23.1	18.4	27.3	33.2	18.7	45.2	69.2	27.6	32.0	62.5	0.0
SE	Num	1	1,009	736	1	22	43	2	27	129	114	1	1	28	0
	Flex	.00	.00	.00	.16	.43	.64	.43	.24	.48	.64	.25	.45	1.71	0.00
	Rigid	.00	.00	.00	.28	.45	1.03	.60	.33	.79	1.45	.53	.52	2.66	0.00
	GVW	2.8	4.0	3.9	19.6	18.5	30.5	34.6	19.1	40.9	63.1	28.0	45.2	62.0	0.0
NW	Num	2	956	690	1	20	41	3	26	87	142	1	1	18	0
	Flex	.00	.00	.00	.49	.54	.48	.93	.17	1.03	.91	.71	.09	1.78	0.00
	Rigid	.00	.00	.00	.65	.57	.73	1.22	.28	1.90	2.15	1.74	.10	2.40	0.00
	GVW	2.2	3.8	3.9	26.1	18.5	24.1	32.3	18.3	52.3	73.3	32.2	24.2	67.2	0.0
NW Lane1	Num	2	956	690	1	20	41	3	26	87	142	1	1	18	0
	Flex	.00	.00	.00	.49	.54	.48	.93	.17	1.03	.91	.71	.09	1.78	0.00
	Rigid	.00	.00	.00	.65	.57	.73	1.22	.28	1.90	2.15	1.74	.10	2.40	0.00
	GVW	2.2	3.8	3.9	26.1	18.5	24.1	32.3	18.3	52.3	73.3	32.2	24.2	67.2	0.0
SE Lane1	Num	1	1,009	736	1	22	43	2	27	129	114	1	1	28	0
	Flex	.00	.00	.00	.16	.43	.64	.43	.24	.48	.64	.25	.45	1.71	0.00
	Rigid	.00	.00	.00	.28	.45	1.03	.60	.33	.79	1.45	.53	.52	2.66	0.00
	GVW	2.8	4.0	3.9	19.6	18.5	30.5	34.6	19.1	40.9	63.1	28.0	45.2	62.0	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 07/11/2024 11:41 AM

Idaho Transportation Department

Monthly WIM Distribution for Jun-2024

Site names: 00179
County: Power
Funct Class: R Minor Arterial - Other
Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
Daily Factor Grp: 2
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 07/11/2024 11:41 AM