

Idaho Transportation Department

Monthly WIM Distribution for Jul-2024

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,902	1,409	1	38	87	5	49	202	188	2	2	45	0
	Flex	.00	.00	.00	.62	.56	.48	.78	.16	.73	.81	.16	.95	1.15	0.00
	Rigid	.00	.00	.00	.82	.59	.72	1.11	.21	1.29	1.92	.24	1.18	1.71	0.00
	GVW	1.9	3.9	3.9	28.6	18.9	27.4	36.9	18.1	46.7	71.3	26.5	47.4	62.5	0.0
SE	Num	2	966	724	1	18	45	3	25	113	87	2	2	28	0
	Flex	.00	.00	.00	1.00	.48	.56	.68	.14	.43	.74	.19	1.69	1.06	0.00
	Rigid	.00	.00	.00	1.30	.48	.90	1.04	.18	.65	1.67	.22	2.18	1.76	0.00
	GVW	2.1	3.9	4.0	37.3	18.9	29.5	40.0	17.4	39.7	64.3	26.1	67.5	68.1	0.0
NW	Num	2	935	685	1	19	44	2	25	89	101	1	2	17	0
	Flex	.00	.00	.00	.43	.70	.38	.72	.18	1.17	.84	.07	.22	1.45	0.00
	Rigid	.00	.00	.00	.53	.75	.53	.99	.24	2.23	2.05	.14	.22	1.92	0.00
	GVW	1.9	3.9	3.8	24.1	19.2	25.0	35.8	18.7	56.9	75.3	22.4	30.4	59.6	0.0
NW Lane1	Num	2	935	685	1	19	44	2	25	89	101	1	2	17	0
	Flex	.00	.00	.00	.43	.70	.38	.72	.18	1.17	.84	.07	.22	1.45	0.00
	Rigid	.00	.00	.00	.53	.75	.53	.99	.24	2.23	2.05	.14	.22	1.92	0.00
	GVW	1.9	3.9	3.8	24.1	19.2	25.0	35.8	18.7	56.9	75.3	22.4	30.4	59.6	0.0
SE Lane1	Num	2	966	724	1	18	45	3	25	113	87	2	2	28	0
	Flex	.00	.00	.00	1.00	.48	.56	.68	.14	.43	.74	.19	1.69	1.06	0.00
	Rigid	.00	.00	.00	1.30	.48	.90	1.04	.18	.65	1.67	.22	2.18	1.76	0.00
	GVW	2.1	3.9	4.0	37.3	18.9	29.5	40.0	17.4	39.7	64.3	26.1	67.5	68.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2024

Site names:00179

County:Power

Funct Class:R Minor Arterial - Other

Location:I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp:2

Daily Factor Grp:2

Axle Factor Grp:All_Class_Sites

Growth Factor Grp:5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9