Idaho Transportation Department

Monthly WIM Distribution for Dec-2024

Site names: 00179
County: Power
Funct Class: R Minor Arterial - Other
Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
Daily Factor Grp: 2
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,615	1,037	1	33	36	3	15	161	116	2	2	456	0
	Flex	.00	.00	.00	.21	.44	.48	.39	.28	.61	.77	.27	2.17	.83	0.00
	Rigid	.00	.00	.00	.23	.63	.70	.54	.38	1.06	1.76	.59	3.09	1.56	0.00
	GVW	2.0	3.9	4.1	21.0	26.5	27.1	33.6	22.8	46.4	70.4	29.0	74.9	78.9	0.0
SE	Num	1	832	537	1	19	19	2	8	81	59	1	3	232	0
	Flex	.00	.00	.00	.26	.41	.51	.28	.27	.33	.62	.53	2.36	.12	0.00
	Rigid	.00	.00	.00	.25	.57	.77	.40	.40	.49	1.42	1.28	2.92	.16	0.00
	GVW	2.0	3.8	4.1	20.9	26.9	28.3	32.0	21.3	39.0	68.8	36.3	68.4	40.7	0.0
NW	Num	2	783	500	1	14	17	2	8	80	60	1	1	224	0
	Flex	.00	.00	.00	.18	.50	.45	.47	.29	.90	.90	.47	1.71	1.56	0.00
	Rigid	.00	.00	.00	.20	.75	.60	.60	.35	1.65	2.05	.88	2.63	3.02	0.00
	GVW	2.0	3.9	4.0	20.0	26.7	25.6	31.9	23.4	53.9	70.6	32.7	75.6	118.4	0.0
NW Lane1	Num	2	783	500	1	14	17	2	8	80	60	1	1	224	0
	Flex	.00	.00	.00	.18	.50	.45	.47	.29	.90	.90	.47	1.71	1.56	0.00
	Rigid	.00	.00	.00	.20	.75	.60	.60	.35	1.65	2.05	.88	2.63	3.02	0.00
	GVW	2.0	3.9	4.0	20.0	26.7	25.6	31.9	23.4	53.9	70.6	32.7	75.6	118.4	0.0
SE Lane1	Num	1	832	537	1	19	19	2	8	81	59	1	3	232	0
	Flex	.00	.00	.00	.26	.41	.51	.28	.27	.33	.62	.53	2.36	.12	0.00
	Rigid	.00	.00	.00	.25	.57	.77	.40	.40	.49	1.42	1.28	2.92	.16	0.00
	GVW	2.0	3.8	4.1	20.9	26.9	28.3	32.0	21.3	39.0	68.8	36.3	68.4	40.7	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 01/02/2025 11:23 AM

Idaho Transportation Department

Monthly WIM Distribution for Dec-2024

Site names: 00179
County: Power
Funct Class: R Minor Arterial - Other
Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
Daily Factor Grp: 2
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 01/02/2025 11:23 AM