

Idaho Transportation Department

Monthly WIM Distribution for Jan-2024

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 8

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	96	94	1	4	14	2	5	14	20	2	1	4	0
	Flex	.00	.00	.00	.17	.19	.63	.61	1.06	1.51	.76	1.56	.46	.99	0.00
	Rigid	.00	.00	.00	.26	.19	.91	1.03	1.33	2.58	1.44	3.30	.48	1.58	0.00
	GVW	2.7	3.8	4.0	18.4	14.2	27.9	38.7	26.4	56.1	62.6	53.3	40.1	67.1	0.0
E	Num	2	45	45	1	2	8	1	2	7	10	1	1	2	0
	Flex	.00	.00	.00	.20	.24	.75	.24	1.04	2.32	.79	1.16	.43	.68	0.00
	Rigid	.00	.00	.00	.28	.24	1.13	.58	1.49	3.91	1.39	2.48	.45	.79	0.00
	GVW	3.0	3.6	3.6	24.5	14.1	26.9	46.3	28.0	63.8	52.5	45.3	41.4	46.3	0.0
W	Num	1	50	49	1	2	6	1	4	7	10	2	1	3	0
	Flex	.00	.00	.00	.27	.18	.50	1.10	1.00	.64	.71	1.55	.50	1.37	0.00
	Rigid	.00	.00	.00	.47	.18	.67	1.77	1.18	1.13	1.42	3.29	.51	2.34	0.00
	GVW	2.2	4.1	4.4	22.1	14.4	29.4	44.8	25.8	49.6	70.4	53.6	38.8	85.0	0.0
E Lane1	Num	2	45	45	1	2	8	1	2	7	10	1	1	2	0
	Flex	.00	.00	.00	.20	.24	.75	.24	1.04	2.32	.79	1.16	.43	.68	0.00
	Rigid	.00	.00	.00	.28	.24	1.13	.58	1.49	3.91	1.39	2.48	.45	.79	0.00
	GVW	3.0	3.6	3.6	24.5	14.1	26.9	46.3	28.0	63.8	52.5	45.3	41.4	46.3	0.0
W Lane1	Num	1	50	49	1	2	6	1	4	7	10	2	1	3	0
	Flex	.00	.00	.00	.27	.18	.50	1.10	1.00	.64	.71	1.55	.50	1.37	0.00
	Rigid	.00	.00	.00	.47	.18	.67	1.77	1.18	1.13	1.42	3.29	.51	2.34	0.00
	GVW	2.2	4.1	4.4	22.1	14.4	29.4	44.8	25.8	49.6	70.4	53.6	38.8	85.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2024

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 8

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9