

Idaho Transportation Department

Monthly WIM Distribution for May-2024

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 8

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	330	310	1	6	12	3	11	23	23	1	1	5	0
	Flex	.00	.00	.00	.50	.35	.60	.29	.32	.96	.50	.11	2.04	1.24	0.00
	Rigid	.00	.00	.00	.58	.38	.94	.40	.44	1.42	1.09	.16	3.40	2.15	0.00
	GVW	1.4	3.8	4.3	30.6	15.4	27.1	22.7	20.0	48.1	63.4	24.3	42.4	73.3	0.0
E	Num	2	157	150	1	3	8	2	5	12	11	1	1	3	0
	Flex	.00	.00	.00	.59	.36	.85	.41	.38	1.25	.52	.13	2.04	.86	0.00
	Rigid	.00	.00	.00	.64	.39	1.45	.66	.50	1.92	.97	.13	3.40	1.19	0.00
	GVW	1.3	3.8	4.1	31.3	14.9	31.0	27.5	21.2	54.0	50.0	26.9	42.4	50.2	0.0
W	Num	3	173	160	1	3	6	2	6	11	12	1	0	3	0
	Flex	.00	.00	.00	.52	.27	.64	.24	.29	.65	.43	.07	0.00	1.31	0.00
	Rigid	.00	.00	.00	.58	.28	.94	.28	.42	.91	1.09	.13	0.00	2.38	0.00
	GVW	1.4	3.8	4.5	29.2	15.4	29.0	20.9	19.7	42.3	75.4	20.0	0.0	83.4	0.0
E Lane1	Num	2	157	150	1	3	8	2	5	12	11	1	1	3	0
	Flex	.00	.00	.00	.59	.36	.85	.41	.38	1.25	.52	.13	2.04	.86	0.00
	Rigid	.00	.00	.00	.64	.39	1.45	.66	.50	1.92	.97	.13	3.40	1.19	0.00
	GVW	1.3	3.8	4.1	31.3	14.9	31.0	27.5	21.2	54.0	50.0	26.9	42.4	50.2	0.0
W Lane1	Num	3	173	160	1	3	6	2	6	11	12	1	0	3	0
	Flex	.00	.00	.00	.52	.27	.64	.24	.29	.65	.43	.07	0.00	1.31	0.00
	Rigid	.00	.00	.00	.58	.28	.94	.28	.42	.91	1.09	.13	0.00	2.38	0.00
	GVW	1.4	3.8	4.5	29.2	15.4	29.0	20.9	19.7	42.3	75.4	20.0	0.0	83.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2024

Site names: 00185

County: Idaho

Funct Class: R Principal Arterial - Other

Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10

Daily Factor Grp: 5

Axle Factor Grp: All_Class_Sites

Growth Factor Grp: 8

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9